


IE5369

IEB3004-BPKG/V4A/2M

Inductive sensors

Product characteristics

Inductive sensor

Metal thread M8 x 1

Cable

Sensing range 4 mm; [nf] non-flush mountable

Electrical data

Electrical design	DC PNP
Operating voltage [V]	10...30 DC; "supply class 2" to cULus.
Current consumption [mA]	< 15
Protection class	III
Reverse polarity protection	yes

Outputs

Output function	normally open
Voltage drop [V]	< 2.5
Current rating [mA]	100
Short-circuit protection	pulsed
Overload protection	yes
Switching frequency [Hz]	500

Range

Sensing range [mm]	4
Real sensing range (Sr) [mm]	4 ± 10 %
Operating distance [mm]	0...3.25

Accuracy / deviations

Correction factors	mild steel = 1 / stainless steel approx. 0.7 / brass approx. 0.5 / Al approx. 0.4 / Cu approx. 0.3
Hysteresis [% of Sr]	1...15
Switch-point drift [% of Sr]	-10...10

Environment

Ambient temperature [°C]	0...60
Protection	IP 67

Tests / approvals

EMC	EN 60947-5-2
MTTF [Years]	3408

Mechanical data

Mounting	non-flush mountable
Housing materials	high-grade stainless steel; active face: LCP
Weight [kg]	0.047

Displays / operating elements

IE5369

IEB3004-BPKG/V4A/2M

Inductive sensors

Output status indication	LED	yellow
--------------------------	-----	--------

Electrical connection

Connection	PUR cable / 2 m; 3 x 0.14 mm ²
------------	---


Wiring

Core colours

BK black

BN brown

BU blue



Accessories

Accessories (included)	2 lock nuts
------------------------	-------------

Remarks

Pack quantity	[piece]	1
---------------	---------	---