


FOOT MASTER®

Shock absorbing casters

GDSP series

 360~450kg  RoHS  -10~90°C











Towing by power vehicle(20km/h)

Brackets: Pressed steel plate, double ball bearing with hardened bearing seats in the swivel head, strong welded frame, fine shock absorption function with special rubber, towing by power vehicle(20km/h), steel top brake system, bolted wheel axle structure

Surface Treatment: Zinc plated

* Recommended Load = Load Cap. × 3

Swivel	Rigid	Swivel with brake	Rigid with brake	Wheel type	Cushion	 mm	 mm	 Kg	 mm	 mm	 mm	 mm	 mm
GDSP-150-ASF	GDSP-150-ARF	GDSP-150-BSF	GDSP-150-BRF	MUD	65°	150	48	360	202-14	48~53	158x114	133x86 125x62	13
GDSP-200-ASF	GDSP-200-ARF	GDSP-200-BSF	GDSP-200-BRF		75°	200	48	450	253-15	65~75			
GDSP-150-ASF-PEU	GDSP-150-ARF-PEU	GDSP-150-BSF-PEU	GDSP-150-BRF-PEU	MUD	65°	150	48	360	202-14	48~53	140x110	105x80 105x75	11
GDSP-200-ASF-PEU	GDSP-200-ARF-PEU	GDSP-200-BSF-PEU	GDSP-200-BRF-PEU		75°	200	48	450	253-15	65~75			

Options

						
Code Suffix	MUD	-2DL	-4DL			
Description	Cast PU(A95)	2 Directional Lock	4 Directional Lock			
Available for	150 ~ 200	150 ~ 200	150 ~ 200			