

SIMATIC DP, 1 ELECTRON. MODULE FOR ET 200S, 8 DO  
DC24V/0,5A, 15 MM WIDTH, 1 PIECE PER PACKAGING UNIT



Figure similar

Supply voltage	
Reverse voltage protection	Yes
Load voltage L+	
• Rated value (DC)	24 V
• Reverse polarity protection	Yes
Input current	
from load voltage L+ (without load), max.	5 mA; Per channel
from backplane bus 3.3 V DC, max.	10 mA
Power loss	
Power loss, typ.	1.5 W
Address area	
Address space per module	
• without packing	1 byte
Digital outputs	
Number of digital outputs	8
Short-circuit protection	Yes

• Response threshold, typ.	o.k.
Limitation of inductive shutdown voltage to	o.k.
Controlling a digital input	Yes
<b>Switching capacity of the outputs</b>	
• on lamp load, max.	5 W
<b>Load resistance range</b>	
• lower limit	48 Ω
• upper limit	3 400 Ω
<b>Output voltage</b>	
• for signal "1", min.	o.k.
<b>Output current</b>	
• for signal "1" rated value	0.5 A
• for signal "1" permissible range, min.	7 mA
• for signal "1" permissible range, max.	600 mA
• for signal "0" residual current, max.	0.3 mA
<b>Output delay with resistive load</b>	
• "0" to "1", max.	300 μs
• "1" to "0", max.	600 μs
<b>Parallel switching of two outputs</b>	
• for uprating	No
<b>Switching frequency</b>	
• with resistive load, max.	100 Hz
• with inductive load, max.	2 Hz
• on lamp load, max.	10 Hz
<b>Total current of the outputs</b>	
• Current per module, max.	4 A
<b>Cable length</b>	
• shielded, max.	1 000 m
• unshielded, max.	600 m
<b>Isochronous mode</b>	
Isochronous operation (application synchronized up to terminal)	Yes; jitter incumbered < 100us
<b>Interrupts/diagnostics/status information</b>	
Diagnostic functions	No
<b>Diagnostics indication LED</b>	
• Status indicator digital output (green)	Yes
<b>Parameter</b>	
Remark	3-byte parameter (not accessible for the user)
<b>Potential separation</b>	
<b>Potential separation digital outputs</b>	
• between the channels	No

- between the channels and backplane bus

Yes

### Isolation

Isolation tested with

500 V DC

### Dimensions

Width

15 mm

Height

81 mm

Depth

52 mm

### Weights

Weight, approx.

40 g

**last modified:**

12/24/2016