

Bảng thông số sản phẩm

Thông số kỹ thuật



Zencelo - 250V LED INDICATOR RD

8430SNRD_WE_G19

Main

Range	ZENcelo
Product or component type	Message indicator
Local signalling	Indicator light, LED (red)
Colour tint	White

Complementary

Clamping connection capacity	1 x 1...4 x 1 mm ² for solid stranded cable(s) 1 x 1.5...5 x 1.5 mm ² for solid stranded cable(s) 1 x 2.5...3 x 2.5 mm ² for solid stranded cable(s) 1 x 4...2 x 4 mm ² for solid stranded cable(s)
[Ue] rated operational voltage	250 V AC 50/60 Hz
Material	Brass: metal parts Polycarbonate: base Polycarbonate: cover Polycarbonate: lenses
Connections - terminals	Folded terminal
Width	23.2 mm
Height	45.8 mm
Depth	31.7 mm

Environment

Ambient air temperature for operation	-5...45 °C
Ambient air temperature for storage	0...60 °C
Relative humidity	0...95 %
Environmental characteristic	UV resistant
Operating altitude	<= 2000 m
IP degree of protection	IP20

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes

EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile

Thay thế được đề xuất

Bảng thông số sản phẩm

Thông số kỹ thuật



Zencelo - 250V LED INDICATOR RD

8430SNRD_BZ_G19

Main

Range	ZENcelo
Product or component type	Message indicator
Local signalling	Indicator light, LED (red)
Colour tint	Bronze

Complementary

Clamping connection capacity	1 x 1...4 x 1 mm ² for solid stranded cable(s) 1 x 1.5...5 x 1.5 mm ² for solid stranded cable(s) 1 x 2.5...3 x 2.5 mm ² for solid stranded cable(s) 1 x 4...2 x 4 mm ² for solid stranded cable(s)
[Ue] rated operational voltage	250 V AC 50/60 Hz
Material	Brass: metal parts Polycarbonate: base Polycarbonate: cover Polycarbonate: lenses
Connections - terminals	Folded terminal
Width	23.2 mm
Height	45.8 mm
Depth	31.7 mm

Environment

Ambient air temperature for operation	-5...45 °C
Ambient air temperature for storage	0...60 °C
Relative humidity	0...95 %
Environmental characteristic	UV resistant
Operating altitude	<= 2000 m
IP degree of protection	IP20

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes

EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile

Thay thế được đề xuất