


Standard Socket

KT No. & D1



2330M

- Metric-DIN 3124, ISO 2725-1
- Inch-ANSI/ASME B107.1



2330S 1/4"




KT NO.	mm	D1 mm	D2 mm	l mm	L mm	g	g	g
233004M	4	6.8	11.8	4	24	10	20	600
233045M	4.5	7.4	11.8	5	24	10	20	600
233005M	5	8.0	11.8	6	24	11	20	600
233055M	5.5	8.7	11.8	6	24	11	20	600
233006M	6	9.2	11.8	7	24	11	20	600
233007M	7	10.3	11.8	7	24	11	20	600
233008M	8	11.4	11.8	8	24	11	20	600
233009M	9	12.8	12.0	8	24	15	20	600
233010M	10	14.3	13.0	9	24	14	12	360
233011M	11	15.8	14.2	9	24	20	12	360
233012M	12	16.8	15.5	9	24	22	12	360
233013M	13	17.8	16.5	9	24	24	12	360
233014M	14	19.6	18.5	9	24	30	10	300

KT NO.	inch	D1 mm	D2 mm	l mm	L mm	g	g	g
233005S	5/32	6.8	11.8	4	24	10	20	600
233006S	3/16	7.9	11.8	6	24	10	20	600
233007S	7/32	8.7	11.8	6	24	11	20	600
233008S	1/4	9.5	11.8	7	24	11	20	600
233009S	9/32	10.3	11.8	7	24	11	20	600
233010S	5/16	11.4	11.8	8	24	11	20	600
233011S	11/32	13.7	12.2	8	24	13	20	600
233012S	3/8	14.2	13.0	8	24	14	12	360
233014S	7/16	15.8	14.2	9	24	19	12	360
233015S	15/32	16.8	15.5	9	24	22	12	360
233016S	1/2	17.6	16.5	9	24	24	12	360

2335M

- Metric-DIN 3124, ISO 2725-1
- Inch-ANSI/ASME B107.1



2335S 1/4"



KT NO.	mm	D1 mm	D2 mm	l mm	L mm	g	g	g
233532M	3.2	5.7	11.8	3.5	24	9	20	600
233504M	4	6.8	11.8	4	24	10	20	600
233545M	4.5	7.4	11.8	5	24	10	20	600
233505M	5	8.0	11.8	6	24	11	20	600
233555M	5.5	8.7	11.8	6	24	11	20	600
233506M	6	9.2	11.8	7	24	11	20	600
233507M	7	10.3	11.8	7	24	11	20	600
233508M	8	11.4	11.8	8	24	11	20	600
233509M	9	12.8	12.0	8	24	15	20	600
233510M	10	14.3	13.0	9	24	14	12	360
233511M	11	15.8	14.2	9	24	20	12	360
233512M	12	16.8	15.5	9	24	22	12	360
233513M	13	17.8	16.5	9	24	24	12	360
233514M	14	19.6	18.5	9	24	30	10	300
233515M	15	20.9	19.3	12	24	40	10	300

KT NO.	inch	D1 mm	D2 mm	l mm	L mm	g	g	g
233505S	5/32	6.8	11.8	4	24	10	20	600
233506S	3/16	7.9	11.8	6	24	10	20	600
233507S	7/32	8.7	11.8	6	24	11	20	600
233508S	1/4	9.5	11.8	7	24	11	20	600
233509S	9/32	10.3	11.8	7	24	11	20	600
233510S	5/16	11.4	11.8	8	24	11	20	600
233511S	11/32	13.7	12.2	8	24	13	20	600
233512S	3/8	14.2	13.0	8	24	14	12	360
233514S	7/16	15.8	14.2	9	24	19	12	360
233515S	15/32	16.8	15.5	9	24	22	12	360
233516S	1/2	17.6	16.5	9	24	24	12	360
233518S	9/16	19.6	18.5	9	24	25.2	10	300

Deep Socket

2235M


- DIN 3124, ISO 2725-1



KT NO.	mm	D1 mm	D2 mm	l mm	L mm	g	g	g
223504M	4	6.9	11.6	6	49.5	20	20	320
223545M	4.5	7.5	11.6	6	49.5	21	20	320
223505M	5	8.0	11.6	7	49.5	21	20	320
223555M	5.5	8.8	11.6	7	49.5	21	20	320
223506M	6	9.5	11.6	8	49.5	23	20	320
223507M	7	10.5	11.6	12	49.5	23	20	320
223508M	8	11.8	11.8	15	50	24	20	320
223509M	9	13.0	13.0	15	50	29	15	240
223510M	10	14.5	14.5	15	50	38	15	240
223511M	11	15.8	15.8	21	50	44	15	240
223512M	12	16.8	16.8	21	50	53	15	240
223513M	13	17.8	17.8	21	50	51	15	240
223514M	14	19.8	19.8	21	50	68	15	240
223515M	15	20.9	20.9	25	50	79	12	240

2235S

1/4"



KT NO.	inch	D1 mm	D2 mm	l mm	L mm	g	g	g
223505S	5/32	6.8	11.8	6	50	24	20	320
223506S	3/16	7.9	11.8	7	50	24	20	320
223507S	7/32	8.7	11.8	9	50	25	20	320
223508S	1/4	9.5	11.8	9	50	25	20	320
223509S	9/32	10.3	11.8	15	50	25	20	320
223510S	5/16	11.8	11.8	15	50	24	20	320
223511S	11/32	13.0	13.0	15	50	31	15	240
223512S	3/8	14.5	14.5	15	50	34	15	240
223514S	7/16	15.8	15.8	21	50	46	15	240
223516S	1/2	17.6	17.6	21	50	56	15	300
223518S	9/16	19.6	19.6	21	50	52.2	15	270