



## DCH253M2

#### 18V XR Li-Ion Heavy Duty 3 Mode Dedicated Cordless Hammer

## **Selling Proposition**

- Ideal for drilling anchors and fixing holes into concrete, brick and masonry from 4mm to 24mm
- Rotation stop mode for light chiselling in plaster, tiles and render and impact stop mode for rotary only drilling in wood and metal
- 4.0Ah 18 Volt Lithium Ion battery, delivers high performance, long life and maximum runtime
- Best in class vibration, 6.6m/s<sup>2</sup> reduces user fatigue and maximises operating periods
- Bright white LED with delay feature improves visibility

## **Standard Equipment**

- 2 x 4.0Ah XR Li-Ion battery packs with state of charge indicator
- Multi-voltage XR charger
- Multi-position side handle
- Heavy duty kitbox

## Warranty Specifications

- 30 Day No Risk Satisfaction Guarantee
- 3 year limited warranty
- 1 Year Free Service Contract

Specifications	
Battery chemistry	XR Li-Ion
Voltage	18 V
Kapazität	4.0 Ah
Abgabeleistung	400 Watt
No Load Speed	0-1200 rpm
Impact energy (EPTA 05/2009)	2.1 J
Blows per Minute	0-4500 bpm
Tool Holder	SDS-Plus





# DCH273P2

# 18V XR Li-Ion Brushless 3 Mode Dedicated Cordless Hammer

## **Selling Proposition**

- Category-leading high speed drilling performance at more than 90 holes (10mm  $\emptyset$  x 80mm) per charge
- Rotation stop mode for light chiselling in plaster, tiles and render and impact stop mode for rotary only drilling in wood and metal
- Brushless motor with high capacity XR 5.0Ah 18V Lithium-ion battery platform for extreme runtime and reduced maintenance
- Electronic clutch for consistently-high torque and improved durability
- Perform & Protect: best-in-class vibration at 6.6m/s<sup>2</sup>, minimising user fatigue
- Bright white LED with delay feature improves visibility

#### Standard Equipment

- 2 x 5.0Ah XR Li-Ion battery packs with state of charge indicator
- Multi-voltage XR charger
- Belt hook
- Multi-position side handle
- Heavy duty kitbox

## Warranty Specifications

- 30 Day No Risk Satisfaction Guarantee
- 3 year limited warranty
- 1 Year Free Service Contract

Specifications	
Battery chemistry	XR Li-Ion
Voltage	18 V
Battery Capacity	5.0 Ah
Power Output	400 Watt
No Load Speed	0-1100 rpm
Impact energy (EPTA 05/2009)	2.1 J
Blows per Minute	0-4600 bpm
Tool Holder	SDS-Plus