

Product variant	Scanning range	Working range	Horizontal aperture angle	Angular resolution (horizontal)	Application	Communication interface	Digital outputs	Task	Certificate
LD-LRS3611	250 m	5 m ... 250 m	360 °	0.0625, 0.125, 0.1875, 0.25, 0.375, 0.5, 0.75, 1 °	Outdoor, Indoor	Ethernet, Serial	1	Measuring - Dimension, contour and volume, Protecting objects	EU declaration of conformity, UK declaration of conformity, ACMA declaration of conformity, China-RoHS
LD-LRS3600	250 m	2.5 m ... 250 m	360 °	0.0625, 0.125, 0.1875, 0.25, 0.375, 0.5, 0.75, 1 °	Outdoor, Indoor	Ethernet, Serial	4	Buildings and grounds, Protecting objects - Infrastructure, Determining position - 2D position determination	EU declaration of conformity, UK declaration of conformity, ACMA declaration of conformity, China-RoHS
LD-LRS3601	250 m	2.5 m ... 250 m	360 °	0.0625, 0.125, 0.1875, 0.25, 0.375, 0.5, 0.75, 1 °	Outdoor, Indoor	Ethernet, Serial	1		EU declaration of conformity, UK declaration of conformity, ACMA declaration of conformity, China-RoHS, KC Mark certificate