






Guide for selection of wheels : AGV casters

Image	Series	Description	Wheel code	Wheel dia mm	Wheel width mm	Axle bore mm	Hub length mm	Load capacity Kg	Bearing type
	HUD	<ul style="list-style-type: none"> – Cast polyurethane (Shore A90) – Aluminum core – Two ball bearings 	HUD-75-30	75	30	8	30	100	608 ZZ
			HUD-75-23	75	23	15	23	100	6202 ZZ
			HUD-75-48	75	48	15	51	200	6202 ZZ
	HUD	<ul style="list-style-type: none"> – Cast polyurethane (Shore A95) – Steel core – Two ball bearings 	HUD-75-30	75	30	15	30	125	6202 ZZ
			HUD-100-30	100	30	15	30	155	6202 ZZ
			HUD-125-35	125	35	15	35	220	6202 ZZ
			HUD-150-40	150	40	15	40	315	6202 ZZ
	NUD	<ul style="list-style-type: none"> – Cast polyurethane (Shore A95) – Steel core – Two ball bearings 	NUD-75-30	75	30	15	30	125	6202 ZZ
			NUD-100-30	100	30	15	30	155	6202 ZZ
			NUD-125-35	125	35	15	35	220	6202 ZZ
			NUD-150-40	150	40	15	40	315	6202 ZZ

AGV casters GSAD series

kg 400~600kg **RoHS** **TEMP** -10~90°C



Brackets: Steel plate, double precision ball bearing in the swivel head to optimize heavy load, strong welded frame, self-aligned function with two swiveling axes with different swiveling radii, bolted wheel axle structure

Surface Treatment: Powder coating, zinc plated

* Recommended Load = Load Cap. × 3

Swivel	Wheel type	mm	mm	Kg	mm	mm	mm	mm	mm
GSAD-110-ASF	HUD	110	29x2	400	190	15~35	112x112	92x92	9
GSAD-150-ASF	HUD	150	40x2	600	235	15~35	145x130	115x100	11

Options

Code Suffix	HUD								
Description	Cast PU(A95)								
Available for	110 ~ 150								



Product movie