


Special plugs and sockets – SCHUKO® and grounding-type


SCHUKO® to DIN 49440-1, 2 p+E, 230 V. Other versions available on request. For drawings and dimensions see page 102 - 110.



Panel mounted socket grounding-type
French/Belgian system (NF), without hinged lid, 3 plug-in terminals or 3 screw terminals as connecting terminals for 1.5 - 2.5 mm²

IP 20
Std. Pack. Qty: 100/20
Drawing: 1 MB 450


Colour	Ampere	Voltage	with shutter	plug-in terminals	screw terminals
blue	16	230	✓	11611	
blue	16	230		11661	11681



Panel mounted socket grounding-type
British standard, with hinged lid and seal; flange 50 x 50 mm, fixing holes 38 x 38 mm

IP 44
Std. Pack. Qty: 20
Drawing: 1 MB 584


Colour	Ampere	Voltage	with shutter	plug-in terminals	screw terminals
blue	13	230	✓		10718



Panel mounted socket grounding-type
British standard, matching cover frame, with hinged lid and seal

IP 44
Std. Pack. Qty: 20
Drawing: 1 MB 422

Colour	Ampere	Voltage	with shutter	plug-in terminals	screw terminals
black	13	230	✓		10713




Panel mounted socket NEMA
USA and Canada, with hinged lid

IP 44
Std. Pack. Qty: 20
Drawing: 1 MB 421

Colour	Ampere	Voltage	with shutter	plug-in terminals	screw terminals
blu	15	125			10087


5



Plug SCHUKO®
with combined PE-conductor acc. to German and French/Belgian standards, with grommet, for cables up to 3 x 2.5 mm² up to H07RN-F

IP 44
Std. Pack. Qty: 20

Colour	Ampere	Voltage	Part no.
grey	16	230	10749
black	16	230	10754
orange	16	230	10837
blue	16	230	10838
red	16	230	10839
yellow	16	230	10840
green	16	230	10841



Connector SCHUKO®
with grommet and lid for cables up to 3 x 2.5 mm² up to H07RN-F

IP 44
Std. Pack. Qty: 10

Colour	Ampere	Voltage	Part no.
grey	16	230	10751
black	16	230	10755
orange	16	230	10842
blue	16	230	10843
red	16	230	10844
yellow	16	230	10845
green	16	230	10846