


Part no. 10846



- screw terminals •
 - with grommet and lid
- for cables up to 3 x 2.5 mm², up to H07RN-F .

Technical specifications

Ampere	16 A
Poles	2 p+E
Voltage	230 V
Connection technology	Screw terminals
Contact	standard
Protection type	IP 44
Shutter	false
Weight	83 g
Declaration of Conformity	VDE, EAC






Part no. 10845



- screw terminals •
 - with grommet and lid
- for cables up to 3 x 2.5 mm², up to H07RN-F

Technical specifications

Ampere	16 A
Poles	2 p+E
Voltage	230 V
Connection technology	Screw terminals
Contact	standard
Protection type	IP 44
Shutter	false
Weight	83 g
Declaration of Conformity	VDE, EAC






Part no. 10844



- screw terminals •
 - with grommet and lid
- for cables up to 3 x 2.5 mm², up to H07RN-F .

Technical specifications

Ampere	16 A
Poles	2 p+E
Voltage	230 V
Connection technology	Screw terminals
Contact	standard
Protection type	IP 44
Shutter	false
Weight	83 g
Declaration of Conformity	VDE, EAC






Part no. 10843



- screw terminals •
 - with grommet and lid
- for cables up to 3 x 2.5 mm², up to H07RN-F .

Technical specifications

Ampere	16 A
Poles	2 p+E
Voltage	230 V
Connection technology	Screw terminals
Contact	standard
Protection type	IP 44
Shutter	false
Weight	83 g
Declaration of Conformity	VDE, EAC






Part no. 10842



- screw terminals •
 - with grommet and lid
- for cables up to 3 x 2.5 mm², up to H07RN-F .

Technical specifications

Ampere	16 A
Poles	2 p+E
Voltage	230 V
Connection technology	Screw terminals
Contact	standard
Protection type	IP 44
Shutter	false
Weight	82 g
Declaration of Conformity	VDE, EAC





Part no. 10755




screw terminals

•

- with grommet and lid
- for cables up to 3 x 2.5 mm², up to H07RN-F

Technical specifications

Ampere	16 A
Poles	2 p+E
Voltage	230 V
Connection technology	Screw terminals
Contact	standard
Protection type	IP 44
Shutter	false
Weight	80 g
Declaration of Conformity	VDE, EAC





Part no. 10751



screw terminals

•

- with grommet and lid
- for cables up to 3 x 2.5 mm², up to H07RN-F

Technical specifications

Ampere	16 A
Poles	3 p
Voltage	230 V
Connection technology	Screw terminals
Contact	standard
Protection type	IP 44
Shutter	false
Weight	82 g
Declaration of Conformity	VDE, EAC

