


Material: Copper tube (Cu) 99% up
Surface: Tin plated
Range size (mm²): 1.5-1000

No.	Items	Dimension (mm)			Thickness (mm)	Weight (g)
		d2	d1	D		
1	SL15	2.2		18	0.8	1.1
2	SL25	2.4	3.9	18	0.8	1.17
3	SL4-4	2.8	4.5	20	0.9	1.71
4	SL6	3.8	5.5	24	0.9	2.62
5	SL10	4.5	6.2	25	0.9	3.14
6	SL16	5.4	7.1	29	0.9	4.25
7	SL25	6.8	8.8	29	1	6.25
8	SL35	8.2	10.6	35	1.2	10.91
9	SL50	9.5	12.4	35	1.5	15.36
10	SL70	11.2	14.7	45	1.8	28.19
11	SL95	13.5	17.4	47	2	39.14
12	SL120	15	19.4	52	2.2	54.39
13	SL150	16.5	21.2	59	2.4	72.25
14	SL185	18.5	23.5	65	2.5	94.34
15	SL240	21	26.5	75	2.8	135.42
16	SL300	23.5	30	90	3.3	216.3
17	SL400	28.5	36.5	105	4	377.36
18	SL500	30	39	105	4.5	450.7
19	SL630	34.5	44	120	4.8	618.5
20	SL800	40	51.2	140	5.6	988.35
21	SL1000	44	56.6	160	6.3	1,401.70



Insulation: Vinyl
Plating: Tin
Material: Copper or brass
Range size (mm²): 0.5 - 6

Items	Din (mm ²)	Dimension (mm)					
		d2	B	L	F	H	D
RV125-3	0.5-15	3.2	5.7	17.8	5.0	10.0	4.3
RV125-4	0.5-15	4.3	6.6	20.1	6.3	10.0	4.3
RV125-5	0.5-15	5.3	8.0	21.5	7.0	10.0	4.3
RV125-6	0.5-15	6.4	9.8	23	8.5	10.0	4.3
RV125-8	0.5-15	8.4	11.6	27.5	11.1	10.0	4.3
RV125-10	0.5-15	10.5	13.6	31.6	13.9	10.0	4.3
RV125-12	0.5-15	13.0	19.2	36.0	16.5	10.0	4.3
RV2-3	1.5-2.5	3.2	6.6	17.8	4.3	10.0	4.9
RV2-4	1.5-2.5	4.3	6.6	21	7.0	10.0	4.9
RV2-5	1.5-2.5	5.3	8.5	22.5	7.8	10.0	4.9
RV2-6	1.5-2.5	6.4	12	27.6	11.0	10.0	4.9
RV2-8	1.5-2.5	8.4	12	27.6	11.0	10.0	4.9
RV2-10	1.5-2.5	10.5	13.6	30.2	13.9	10.0	4.9
RV2-12	1.5-2.5	13.0	19.2	36.5	16.5	10.0	4.9
RV3.5-4	2.5-4	4.3	8.0	24.5	7.7	13.0	6.2
RV3.5-5	2.5-4	5.3	8.0	24.5	7.7	13.0	6.2
RV3.5-6	2.5-4	6.4	12.0	27.9	7.7	13.0	6.2
RV5.5-5	4-6	5.3	9.5	25.5	8.3	13.0	6.7
RV5.5-6	4-6	6.4	12.0	31.5	13.0	13.0	6.7
RV5.5-8	4-6	8.4	15.0	33.7	13.7	13.0	6.7
RV5.5-10	4-6	10.5	15.0	33.7	13.7	13.0	6.7
RV5.5-12	4-6	13	19.2	38.1	16.0	13.0	6.7