


●汎用コーティングコバルトドリルです。

This is general coated cobalt HSS drills having jobbers length.



新商品

オーダー方法 GCOSD 直径

単位 (Unit) : mm

直径 Dc	溝長 ℓ	全長 L	在庫 Stock	直径 Dc	溝長 ℓ	全長 L	在庫 Stock	直径 Dc	溝長 ℓ	全長 L	在庫 Stock	直径 Dc	溝長 ℓ	全長 L	在庫 Stock
1.0	12	34		1.6				2.2				2.8			
1.01				1.61				2.21				2.81			
1.02				1.62				2.22				2.82			
1.03				1.63				2.23				2.83			
1.04				1.64				2.24				2.84	25	67	
1.05				1.65	16	43		2.25				2.85			
1.06				1.66				2.26				2.86			
1.07				1.67				2.27				2.87			
1.08				1.68				2.28				2.88			
1.09				1.69				2.29				2.89			
1.1				1.7				2.3	21	58		2.9			
1.11	13			1.71				2.31				2.91			
1.12				1.72				2.32				2.92			
1.13				1.73				2.33				2.93			
1.14				1.74				2.34				2.94			
1.15				1.75				2.35				2.95			
1.16				1.76				2.36				2.96			
1.17				1.77				2.37				2.97			
1.18				1.78				2.38				2.98			
1.19				1.79				2.39				2.99			
1.2				1.8				2.4				3.0			
1.21				1.81	18	46		2.41				3.01			
1.22				1.82				2.42				3.02			
1.23				1.83				2.43				3.03			
1.24				1.84				2.44				3.04			
1.25	14			1.85				2.45				3.05			
1.26				1.86				2.46				3.06			
1.27				1.87				2.47	23	61		3.07			
1.28				1.88				2.48				3.08			
1.29				1.89				2.49				3.09	27	71	□
1.3			□	1.9				2.5			□	3.1			□
1.31				1.91				2.51				3.11			
1.32				1.92				2.52				3.12			
1.33				1.93				2.53				3.13			
1.34				1.94				2.54				3.14			
1.35				1.95				2.55				3.15			
1.36				1.96				2.56				3.16			
1.37				1.97				2.57				3.17			
1.38				1.98				2.58				3.18			
1.39				1.99				2.59				3.19			
1.4				2.0				2.6				3.2			
1.41	15	40		2.01				2.61				3.21			
1.42				2.02				2.62				3.22			
1.43				2.03				2.63				3.23			
1.44				2.04				2.64				3.24			
1.45				2.05	19			2.65				3.25			
1.46				2.06				2.66				3.26			
1.47				2.07				2.67				3.27			
1.48				2.08				2.68				3.28			
1.49				2.09				2.69				3.29			
1.5				2.1				2.7				3.3			
1.51				2.11		55		2.71				3.31			
1.52				2.12				2.72				3.32			
1.53				2.13				2.73				3.33			
1.54				2.14				2.74				3.34			
1.55	16	43		2.15				2.75	25	67		3.35	29	73	
1.56				2.16				2.76				3.36			
1.57				2.17				2.77				3.37			
1.58				2.18				2.78				3.38			
1.59				2.19				2.79				3.39			

超硬ドリル

ハイスドリル

タップ

超硬
エンドミル

ハイス
エンドミル

切断工具

パック・
セット商品
その他

精密工具

技術資料
索引

Next Page 次頁 →

← 前頁 Previous Page

単位 (Unit) : mm

- 新品
- 超硬ドリル
- ハイスドリル
- タップ
- 超硬
エンドミル
- ハイス
エンドミル
- 切断工具
- パック・
セット商品
その他
- 精密工具
- 技術資料
索引

直径 Dc	溝長 ℓ	全長 L	在庫 Stock
3.4	29	73	
3.41			
3.42			
3.43			
3.44			
3.45			
3.46			
3.47			
3.48			
3.49			
3.5			
3.51			
3.52			
3.53			
3.54			
3.55			
3.56			
3.57			
3.58			
3.59			
3.6	31	76	
3.61			
3.62			
3.63			
3.64			
3.65			
3.66			
3.67			
3.68			
3.69			
3.7			
3.71			
3.72			
3.73			
3.74			
3.75			
3.76			
3.77			
3.78			
3.79			
3.8	33	79	
3.81			
3.82			
3.83			
3.84			
3.85			
3.86			
3.87			
3.89			
3.9			
3.91			
3.92			
3.93			
3.94			
3.95			
3.96			
3.97			
3.98			
3.99			
4.0	35	83	
4.05			
4.1			
4.15			
4.2			
4.25			
4.3			
4.35			
4.4			
4.45			
4.5			

直径 Dc	溝長 ℓ	全長 L	在庫 Stock
4.55	36	86	
4.6			
4.65			
4.7			
4.75			
4.8	38	89	
4.85			
4.9			
4.95			
5.0			
5.05	40	92	
5.1			
5.15			
5.2			
5.25			
5.3	42	95	
5.35			
5.4			
5.45			
5.5			
5.55	44	98	
5.6			
5.65			
5.7			
5.75			
5.8	46	102	
5.85			
5.9			
5.95			
6.0			
6.05	47	105	
6.1			
6.15			
6.2			
6.25			
6.3	49	108	
6.35			
6.4			
6.45			
6.5			
6.55	51	111	
6.6			
6.65			
6.7			
6.75			
6.8	53	114	
6.85			
6.9			
6.95			
7.0			
7.05	55	117	
7.1			
7.15			
7.2			
7.25			
7.3	57	121	
7.35			
7.4			
7.45			
7.5			
7.55	58	124	
7.6			
7.65			
7.7			
7.75			
7.8	60	127	
7.85			
7.9			
7.95			
8.0			

直径 Dc	溝長 ℓ	全長 L	在庫 Stock
8.05	55	117	
8.1			
8.15			
8.2			
8.25			
8.3	57	121	
8.35			
8.4			
8.45			
8.5			
8.55	58	124	
8.6			
8.65			
8.7			
8.75			
8.8	60	127	
8.85			
8.9			
8.95			
9.0			
9.05	62	130	
9.1			
9.15			
9.2			
9.25			
9.3	64	133	
9.35			
9.4			
9.45			
9.5			
9.55	65	137	
9.6			
9.65			
9.7			
9.75			
9.8	67	140	
9.85			
9.9			
9.95			
10.0			
10.05	69	143	
10.1			
10.15			
10.2			
10.25			
10.3	71	146	
10.35			
10.4			
10.45			
10.5			
10.55	72	149	
10.6			
10.65			
10.7			

直径 Dc	溝長 ℓ	全長 L	在庫 Stock
10.75	67	140	
10.8			
10.85			
10.9			
10.95			
11.0	69	143	
11.05			
11.1			
11.15			
11.2			
11.25	71	146	
11.3			
11.35			
11.4			
11.45			
11.5	72	149	
11.55			
11.6			
11.65			
11.7			
11.75	74	152	
11.8			
11.85			
11.9			
11.95			
12.0	76	155	
12.05			
12.1			
12.15			
12.2			
12.25	78	158	
12.3			
12.35			
12.4			
12.45			
12.5	80	161	
12.55			
12.6			
12.65			
12.7			
12.75	82	164	
12.8			
12.85			
12.9			
12.95			
13.0	84	167	

一般 構造用鋼	炭素鋼	合金鋼 調質鋼	ダイス鋼 プレハードン鋼	高硬度鋼	
SS400	S45C S50C	SCM NAK	30~40 HRC	40~50 HRC	50~65HRC
○	◎	◎	○	×	×
ステンレス鋼			Ti 合金 耐熱合金	鋳鉄	アルミ合金 銅合金
SUS304 SUS316	SUS420	Ti / Ni Alloy	FC / FCD	AC / ADC	Cu
○	○	—	○	○	○

◎:最適 Excellent ○:適用 Good ×:不適 Not Used —:推奨しません Not recommended