

INSTITUTIONAL MEDIUM - DUTY

270 URY SERIES

90 ~ 135 KGS
In compliance to Korean Standard Specification




UBY PU Blue
Available on request

Castor 270

Armor steel, double ballrace swivel path
frame heat treatment. Metal thickness: 2.5mm
Finish: Zinc plated

Wheel URY

Polyurethane, red non-marking
PP core double precision ball bearing (with plastic threadguards)
Quiet rolling, abrasive, impact, water and chemical resistance
Hardness 92 ~ 95± Shore A. Temperature Range: -20°C to +90°C



Threaded stem	mm/inch	mm	mm	mm	mm	mm	mm	mm	mm	bearing	kgs
271 URY 075 T12/T13	M12 / 1/2"-20 UNF	30	107	34	75	32	10.1	40	40		90
271 URY 100 T12/T13	M12 / 1/2"-20 UNF	30	137	32.5	100	32	10.1	40	40		100
271 URY 125 T12/T13	M12 / 1/2"-20 UNF	30	164	32.5	125	32	10.1	40	40		120
271 URY 150 T12/T13	M12 / 1/2"-20 UNF	30	197	35	150	32	10.1	40	40		135

Threaded Stem with Side-Brake	mm/inch	mm	mm	mm	mm	mm	mm	mm	mm	bearing	kgs
273 URY 075 T12/T13	M12 / 1/2"-20 UNF	30	107	34	75	32	10.1	40	40		90
273 URY 100 T12/T13	M12 / 1/2"-20 UNF	30	137	32.5	100	32	10.1	40	40		100
273 URY 125 T12/T13	M12 / 1/2"-20 UNF	30	164	32.5	125	32	10.1	40	40		120
273 URY 150 T12/T13	M12 / 1/2"-20 UNF	30	197	35	150	32	10.1	40	40		135

Refer to threaded stem specification table on page (00) for reference

Wheels	profile	mm	mm	mm	mm	bush	TG	bearing	kgs	
URY 075	Round	75	32	10.1	40	00	PP		90	
URY 100	Round	100	32	10.1	40	00	PP		100	
URY 125	Round	125	32	10.1	40	00	PP		120	
URY 150	Flat	150	32	10.1	40	00	PP		135	

UBY 075	Round	75	32	10.1	40	00	PP		80
UBY 100	Round	100	32	10.1	40	00	PP		90
UBY 125	Round	125	32	10.1	40	00	PP		105
UBY 150	Flat	150	32	10.1	40	00	PP		120