



子弹形公预绝缘接头
INSULATED MALE BUTTET
DISCONNECTIONS


导线截面: 0.5~1.5mm²(美国线规22-16) 最大电流·Imax=10A 材质: 黄铜

型号	材料厚度 Thickness of material	尺寸 DIMENSION					
		bφ	F	Dφ	dφ	H	L
		mm	mm	mm	mm	mm	mm
MPD 1.25-156	0.4	4.0	11.0	2.7	1.7	10.0	21.0



导线截面: 1.5~2.5mm²(美国线规16-14) 最大电流·Imax=15A

型号 ITEM NO	材料厚度 Thickness of material	尺寸 DIMENSION					
		bφ	F	Dφ	dφ	H	L
		mm	mm	mm	mm	mm	mm
MPD 2-156	0.4	4.0	16.0	3.3	2.3	10.0	21.0
MPD 2-195	0.4	5.0	16.0	3.3	2.3	10.0	21.0



导线截面: 4~6mm²(美国线规12-10) 最大电流·Imax=24A

型号 ITEM NO	材料厚度 Thickness of material	尺寸 DIMENSION					
		bφ	F	Dφ	dφ	H	L
		mm	mm	mm	mm	mm	mm
MPD 5.5-156	0.4	4.0	11.0	4.5	3.4	14.0	25.0
MPD 5.5-195	0.4	5.0	11.0	4.5	3.4	14.0	25.0

子弹形母预绝缘接头
INSULATED RECEPTACLE
DISCONNECTIONS

注: 可依客户制作镀铜套。


导线截面: 0.5~1.5mm²(美国线规22-16) 最大电流·Imax=10A 材质: 黄铜

型号 ITEM NO	材料厚度 Thickness of material	尺寸 DIMENSION						颜色
		bφ	B	Dφ	dφ	F	L	
		mm	mm	mm	mm	mm	mm	
FRD 1.25-156	0.4	4.0	7.7	2.7	1.7	7.3	23	红色 red



导线截面: 1.5~2.5mm²(美国线规16-14) 最大电流·Imax=15A

型号 ITEM NO	材料厚度 Thickness of material	尺寸 DIMENSION					
		bφ	B	Dφ	dφ	F	L
		mm	mm	mm	mm	mm	mm
FRD 2-156	0.4	4.0	7.7	3.3	2.3	7.3	23.8
FRD 2-195	0.4	5.0	8.7	3.3	2.3	7.3	23.8



导线截面: 4~6mm²(美国线规12-10) 最大电流·Imax=24A

型号 ITEM NO	材料厚度 Thickness of material	尺寸 DIMENSION					
		bφ	B	Dφ	dφ	F	L
		mm	mm	mm	mm	mm	mm
FRD 5.5-156	0.4	4.0	7.7	4.5	3.4	7.3	25.5
FRD 5.5-195	0.4	5.0	8.7	4.5	3.4	7.3	25.5