




Replacement LED Bulbs

LED Bulb	Ordering Information	Applicable Products																																				
 <p>Base 9mm Single contact</p>	<p>MAL - T09 - S - 12 - (R)</p> <p>Color</p> <table border="1"> <tr><td>R</td><td>Red</td></tr> <tr><td>Y</td><td>Yellow</td></tr> <tr><td>G</td><td>Green</td></tr> <tr><td>B</td><td>Blue</td></tr> <tr><td>C</td><td>Clear</td></tr> </table> <p>Voltage</p> <table border="1"> <tr><td>12</td><td>12VAC/DC</td></tr> <tr><td>24</td><td>24VAC/DC</td></tr> </table> <p>Current consumption Allowable voltage range</p> <table border="1"> <tr> <td>12V: within 30~50mA</td> <td>12V: 11~13V</td> </tr> <tr> <td>24V: 20mA</td> <td>24V: 22~26V</td> </tr> </table> <p>▲ Pay attention to the polarity if it is DC-type.</p>	R	Red	Y	Yellow	G	Green	B	Blue	C	Clear	12	12VAC/DC	24	24VAC/DC	12V: within 30~50mA	12V: 11~13V	24V: 20mA	24V: 22~26V	<p>MT4 series PS / PL series</p>																		
R	Red																																					
Y	Yellow																																					
G	Green																																					
B	Blue																																					
C	Clear																																					
12	12VAC/DC																																					
24	24VAC/DC																																					
12V: within 30~50mA	12V: 11~13V																																					
24V: 20mA	24V: 22~26V																																					
 <p>Base 15mm Single contact</p>	<p>MAL - T15 - S - 12 - (R)</p> <p>Color</p> <table border="1"> <tr><td>R</td><td>Red</td></tr> <tr><td>Y</td><td>Yellow</td></tr> <tr><td>G</td><td>Green</td></tr> <tr><td>B</td><td>Blue</td></tr> <tr><td>C</td><td>Clear</td></tr> </table> <p>Voltage</p> <table border="1"> <tr><td>12</td><td>12VAC/DC</td></tr> <tr><td>24</td><td>24VAC/DC</td></tr> </table> <p>Current consumption Allowable voltage range</p> <table border="1"> <tr> <td>12V: within 30~50mA</td> <td>12V: 11~13V</td> </tr> <tr> <td>24V: within 20~30mA</td> <td>24V: 22~26V</td> </tr> </table> <p>▲ Pay attention to the polarity if it is DC-type.</p> <hr/> <p>MAL - T15 - S - 110 - (R)</p> <p>Color</p> <table border="1"> <tr><td>R</td><td>Red</td></tr> <tr><td>Y</td><td>Yellow</td></tr> <tr><td>G</td><td>Green</td></tr> <tr><td>B</td><td>Blue</td></tr> <tr><td>C</td><td>Clear</td></tr> </table> <p>Voltage</p> <table border="1"> <tr><td>110</td><td>110VAC</td></tr> <tr><td>220</td><td>220VAC</td></tr> </table> <p>Current consumption Allowable voltage range</p> <table border="1"> <tr> <td>110V: 15mA</td> <td>110V: 100~120V</td> </tr> <tr> <td>220V: 20mA</td> <td>220V: 210~240V</td> </tr> </table>	R	Red	Y	Yellow	G	Green	B	Blue	C	Clear	12	12VAC/DC	24	24VAC/DC	12V: within 30~50mA	12V: 11~13V	24V: within 20~30mA	24V: 22~26V	R	Red	Y	Yellow	G	Green	B	Blue	C	Clear	110	110VAC	220	220VAC	110V: 15mA	110V: 100~120V	220V: 20mA	220V: 210~240V	<p>PR series ML series AS, SL series</p>
R	Red																																					
Y	Yellow																																					
G	Green																																					
B	Blue																																					
C	Clear																																					
12	12VAC/DC																																					
24	24VAC/DC																																					
12V: within 30~50mA	12V: 11~13V																																					
24V: within 20~30mA	24V: 22~26V																																					
R	Red																																					
Y	Yellow																																					
G	Green																																					
B	Blue																																					
C	Clear																																					
110	110VAC																																					
220	220VAC																																					
110V: 15mA	110V: 100~120V																																					
220V: 20mA	220V: 210~240V																																					
 <p>Base 15mm Double contact</p>	<p>MAL - T15 - D - 24 - (R)</p> <p>Color</p> <table border="1"> <tr><td>R</td><td>Red</td></tr> <tr><td>Y</td><td>Yellow</td></tr> <tr><td>G</td><td>Green</td></tr> <tr><td>B</td><td>Blue</td></tr> <tr><td>C</td><td>Clear</td></tr> </table> <p>Voltage</p> <table border="1"> <tr><td>12</td><td>12VAC/DC</td></tr> <tr><td>24</td><td>24VAC/DC</td></tr> </table> <p>Current consumption Allowable voltage range</p> <table border="1"> <tr> <td>12V: within 30~50mA</td> <td>12V: 11~13V</td> </tr> <tr> <td>24V: within 20~30mA</td> <td>24V: 22~26V</td> </tr> </table> <p>▲ Pay attention to the polarity if it is DC-type.</p> <hr/> <p>MAL - T15 - D - 220 - (R)</p> <p>Color</p> <table border="1"> <tr><td>R</td><td>Red</td></tr> <tr><td>Y</td><td>Yellow</td></tr> <tr><td>G</td><td>Green</td></tr> <tr><td>B</td><td>Blue</td></tr> <tr><td>C</td><td>Clear</td></tr> </table> <p>Voltage</p> <table border="1"> <tr><td>110</td><td>110VAC</td></tr> <tr><td>220</td><td>220VAC</td></tr> </table> <p>Current consumption Allowable voltage range</p> <table border="1"> <tr> <td>110V: 15mA</td> <td>110V: 100~120V</td> </tr> <tr> <td>220V: 20mA</td> <td>220V: 210~240V</td> </tr> </table>	R	Red	Y	Yellow	G	Green	B	Blue	C	Clear	12	12VAC/DC	24	24VAC/DC	12V: within 30~50mA	12V: 11~13V	24V: within 20~30mA	24V: 22~26V	R	Red	Y	Yellow	G	Green	B	Blue	C	Clear	110	110VAC	220	220VAC	110V: 15mA	110V: 100~120V	220V: 20mA	220V: 210~240V	<p>MT5 series MT8 series AVG series MSGs series</p>
R	Red																																					
Y	Yellow																																					
G	Green																																					
B	Blue																																					
C	Clear																																					
12	12VAC/DC																																					
24	24VAC/DC																																					
12V: within 30~50mA	12V: 11~13V																																					
24V: within 20~30mA	24V: 22~26V																																					
R	Red																																					
Y	Yellow																																					
G	Green																																					
B	Blue																																					
C	Clear																																					
110	110VAC																																					
220	220VAC																																					
110V: 15mA	110V: 100~120V																																					
220V: 20mA	220V: 210~240V																																					

Please contact the head office for more informations about this product.

Replacement Bulbs

Bulb Type	No	Wattage	Ordering information	Applicable Products
 T10 / BA9S	1	12V 5W	MAB-T09-S-012-05	MT4 series PS / PL series
	2	24V 5W	MAB-T09-S-024-05	
	3	130V 5W	MAB-T09-S-130-05	
	4	240V 5W	MAB-T09-S-240-05	
 G19 / BA15S	5	12V 5W	MAB-T15-S-012-05	AS series SL series
 T16 / BA15S	6	12V 8W	MAB-T15-S-012-08	PR series ML series AS series SL series
	7	24V 8W	MAB-T15-S-024-08	
	8	130V 8W	MAB-T15-S-130-08	
	9	240V 8W	MAB-T15-S-240-08	
 T16 / BA15D	10	12V 10W	MAB-T15-D-012-10	MT5 series MT8 series
	11	24V 10W	MAB-T15-D-024-10	
	12	130V 10W	MAB-T15-D-130-10	
	13	240V 10W	MAB-T15-D-240-10	
 T22 / BA15D	14	12V 25W	MAB-T15-D-012-25	AVG series MSG5 series
	15	24V 25W	MAB-T15-D-024-25	
	16	130V 25W	MAB-T15-D-130-25	AVG series
	17	240V 25W	MAB-T15-D-240-25	
	18	Xenon Lamp 3W	MS86S-LAMP-02 AC/DC 12 ~ 24V I-Type Lamp life: 2,000 hours	MS86S series MS115S series
	19	Xenon Lamp 6W	MS86S-LAMP-10 AC 110V, 220V U-Type Lamp life: 2,000 hours	MS86S series MS115S series