

DATAMAN 8050 SERIES BARCODE READERS

High speed 1D/2D handheld barcode reader

DataMan® 8050 barcode readers bring Cognex's patented algorithms to a new, lightweight industrial handheld platform. DataMan 8050 reads 1D and 2D barcodes with incredible speed every time even if damaged, smudged, scuffed or poorly marked.

Modular design easily adapts to meet your needs

Field interchangeable communication modules allow one reader to be configured to meet specific communication needs to support corded RS-232, USB, and Ethernet options, as well as cordless options including Bluetooth and Wi-Fi.

Rugged industrial design

The DataMan 8050 barcode reader is constructed to handle the harshest environments. Other industrial features include: lanyard hook for easy retractor mounting, bright centralized aimer for clear targeting, loud beeper, and indicator lights.



Proven performance

The DataMan 8050 readers are ideal for applications in any manufacturing environment that require robust barcode technology and reliable reading performance:

- Automotive body and assembly
- Electronics manufacturing
- Incoming inspection
- Shipping
- Automotive kitting
- Aerospace
- Packaging
- Receiving

High speed 1D/2D reading performance

- Cognex's patented algorithms, 1DMax® with Hotbars®, enables the DataMan 8050 barcode reader to decode the most challenging 1D barcodes quickly and easily, at more angles and in any orientation.
- Class-leading 2D algorithms read many 2D symbologies even when damaged, obstructed or with perspective distortion. Supported 2D symbologies include: Data Matrix, QR, PDF417, MaxiCode, and Aztec.
- Best-in-class reading performance means 8050 reads damaged, plastic wrapped, direct inkjet, low contrast, poorly printed, scraped, obstructed, uneven, torn, small, and smudged barcodes.

To learn more about Cognex handheld barcode readers, visit www.cognex.com/handheld



Flexible and easy integration

- Intuitive quick setup allows the user to configure the communication and data formatting settings for many common applications.
- Custom setup sheets can be printed out from within setup tool.
- DataMan setup tool software enables image viewing, complete suite of tools, Java scripting, PERL scripting and a variety of advanced data formatting options.



ESD-Safe Handheld Barcode Readers

DataMan corded ESD-safe handheld barcode readers are designed with electrostatic discharge (ESD) protective housing to prevent costly damage to electronic parts and devices.



SCAN CHART

Type	Depth of Field
7 mil 2D Code	Up to 40 mm
10 mil 2D Code	Up to 80 mm
Code39 6 mil	Up to 90 mm

DATAMAN 8050 SERIES SPECIFICATIONS

Dimensions	210 mm x 115 mm x 85 mm
Weight	Corded: 0.615 lbs./279 g; Wireless: 0.728 lbs./330 g
Operating Temperature	0 °C to 40 °C (32 °F to 104 °F)
Storage Temperature	-40 °C to 60 °C (-40 °F to 140 °F)
Maximum Humidity	95% (non-condensing)
Material	Polycarbonate housing with overmold
Imager	752 x 480 global shutter sensor
Aiming	Centralized green LED aimer
Status Outputs	LED and beeper
Communications	Serial module: RS-232, USB Ethernet module (DataMan 8050E): TCP/IP, FTP, industrial protocols: Ethernet/IP, PROFINET, MC Protocol, ModBus TCP Intelligent base station: RS-232, USB, Ethernet, industrial protocols (optional) Bluetooth module communicates to intelligent base station Wi-Fi module communicates to intelligent Wi-Fi base station
Symbologies	1D: UPC/EAN/JAN; Codabar, Interleaved 2 of 5, Code 39, Code 128, Code 93, GS1 Databar, PDF417, Micro PDF417, Postal Code 2D: Data Matrix, QR, MicroQR, Aztec, MaxiCode
Lighting	Integrated LED with near/far optics
Power Supply Requirements	5 V-6 V DC, 2.5 W LPS or NEC Class 2 power supply Intelligent base station: 24 V DC
Protection	IP-65
Environmental	Compliant with RoHS directive 2002/98/EEC
Regulatory	Electrical CE, CSA, UL, 60950 EMI/RFI FCC Part 15, CE (EMC and R&TTE Directives), ICES-003, RSS-210 Issue 8, KCC
ESD Standards Compliance	IEC 61340-5-1:2016 for select models only
Data Validation	US DoD UID guidelines, GS-1, ISO15434 and ISO15418
Operating System	Microsoft® Windows® XP, Windows 7 and Windows 8

COGNEX

Companies around the world rely on Cognex vision and barcode reading solutions to optimize quality, drive down costs and control traceability.

Corporate Headquarters One Vision Drive Natick, MA 01760 USA

Regional Sales Offices

Americas

North America +1 844-999-2469
Brazil +55 (11) 2626 7301
Mexico +01 800 733 4116

Europe

Austria +49 721 958 8052
Belgium +32 289 370 75
France +33 1 7654 9318
Germany +49 721 958 8052

Hungary +36 800 80291
Ireland +44 121 29 65 163
Italy +39 02 3057 8196
Netherlands +31 207 941 398
Poland +48 717 121 086
Spain +34 93 299 28 14
Sweden +46 21 14 55 88
Switzerland +41 445 788 877
Turkey +90 216 900 1696
United Kingdom +44 121 29 65 163

Asia

China +86 21 6208 1133
India +9120 4014 7840
Japan +81 3 5977 5400
Korea +82 2 539 9980
Malaysia +6019 916 5532
Singapore +65 632 55 700
Taiwan +886 3 578 0060
Thailand +66 88 7978924
Vietnam +84 2444 583358

© Copyright 2019, Cognex Corporation. All information in this document is subject to change without notice. All Rights Reserved. Cognex, Dataman, Hotbars, and 1DMax are registered trademarks of Cognex Corporation. All other trademarks are the property of their respective owners.
Lit. No. DM8050-DS-01-2019

www.cognex.com