


●鋼からステンレス鋼そしてアルミ材まで、高速・高効率加工ができるオイルホールドリルです。

This oil hole drill is adapted in workpiece material from Carbon Steel and Stainless Steel to Aluminum.



LIST 7580P

オーダ方法 **SGOH** 直径

直径8.0~9.9  
在庫品限り

単位 (Unit) : mm

直径 Dc	溝長 ℓ	全長 L	シャンク径 Ds	シャンク長 ℓs	在庫 Stock	参考価格(円) Price (¥)
8.0	56	124	16	48		-
8.1						
8.2						
8.3						
8.4						
8.5	60	128				
8.6						
8.7						
8.8						
8.9						
9.0						
9.1						
9.2						
9.3	65	133				
9.4						
9.5						
9.6						
9.7	70	138				
9.8						
9.9						
10.0						
10.1						
10.2						
10.3						
10.4						
10.5	75	144				
10.6						
10.7						
10.8						
10.9						
11.0						
11.1						
11.2						
11.3						
11.4						
11.5	80	149				
11.6						
11.7						
11.8						
11.9						
12.0						
12.1						
12.2						
12.3						
12.4						
12.5	86	155				
12.6						
12.7						
12.8						
12.9						
13.0						
13.1						
13.2						
13.3						
13.4						
13.5	92	161				
13.6						
13.7						
13.8						
13.9						

直径 Dc	溝長 ℓ	全長 L	シャンク径 Ds	シャンク長 ℓs	在庫 Stock	参考価格(円) Price (¥)
14.0			16	48	●	30,400
14.1						
14.2						
14.3						
14.4						
14.5	97	166				
14.6						
14.7						
14.8						
14.9						
15.0			20	50	●	34,300
15.1						
15.2						
15.3						
15.4						
15.5	102	177				
15.6						
15.7						
15.8						
15.9						
16.0			20	50	●	36,900
16.1						
16.2						
16.3						
16.4						
16.5	107	182				
16.6						
16.7						
16.8						
16.9						
17.0			25	56	●	39,600
17.1						
17.2						
17.3						
17.4						
17.5	113	188				
17.6						
17.7						
17.8						
17.9						
18.0			25	56	●	42,500
18.1						
18.2						
18.3						
18.4						
18.5	118	193				
18.6						
18.7						
18.8						
18.9						
19.0			25	56	●	45,500
19.1						
19.2						
19.3						
19.4						
19.5	123	206				
19.6						
19.7						
19.8						
19.9						

新商品

超硬ドリル

ハイスドリル

タップ

超硬  
エンドミル

ハイス  
エンドミル

切断工具

パック・  
セット商品  
その他

精密工具

技術資料  
索引

単位 (Unit) : mm

直径 Dc	溝長 ℓ	全長 L	シャンク径 Ds	シャンク長 ℓs	在庫 Stock	参考価格(円) Price (¥)												
20.0	128	211	25	56		48,100												
20.5						48,100												
21.0	132	215				32	60	●	51,100									
21.5									51,100									
22.0	137	220							32	60	●	53,900						
22.5												53,900						
23.0	142	225										32	60	●	59,100			
23.5															59,100			
24.0	147	238													32	60	●	63,800
24.5																		63,800
25.0	151	242	32	60	●													67,000
25.5																		67,000
26.0	156	247				32	60	●										70,200
26.5																		70,200
27.0	161	252							32	60	●							73,300
27.5																		73,300
28.0	165	256										32	60	●				76,500
28.5																		76,500
29.0	170	261													32	60	●	79,600
29.5																		79,600
30.0	174	265	32	60	●													81,200

一般 構造用鋼	炭素鋼	合金鋼 調質鋼	ダイス鋼 プレハードン鋼	高硬度鋼	
SS400	S45C S50C	SCM NAK	30 ~ 40 HRC	40 ~ 50 HRC	50 ~ 65HRC
◎	◎	◎	◎	—	×
ステンレス鋼		Ti 合金 耐熱合金	鋳鉄	アルミ合金	銅合金
SUS304 SUS316	SUS420	Ti / Ni Alloy	FC / FCD	AC / ADC	Cu
◎	◎	◎	◎	◎	◎

◎:最適 Excellent ○:適用 Good ×:不適 Not Used —:推奨しません Not recommended