


photo : HS7010

**One-finger trigger switch**  
(HS7010 / HS7610)

**Two-finger trigger switch**  
(HS7611)



**Rear dust exhaust port**

**Flat motor housing design**  
increases stability when changing blades.

**Angular guide at rear**

For smooth and precise adjustment of bevel angle



**Metal plate base**  
(HS7010)

**Aluminum plate base**



(HS7610/HS7611)

**Aluminum diecast safety cover**

**1,600W**

**Continuous rating input**

**Compatible with Guide rail**  
(HS7610 / HS7611)

For use with Guide rail, the shape of base is designed to install Guide rail adapter.



### Accessories

**Guide rail adapter**

(Use with Guide rail)

Part No. 197005-0



**Dust nozzle**

can be attached for use with a vacuum cleaner.

Part No. 196520-1






**Guide rail**



Overall length (m)	Part No.
1.4	194368-5
1.9	194925-9
3	194367-7

## Circular Saw

**HS7010 / HS7610 / HS7611** 185 mm (7-1/4") - 190 mm (7-1/2")

-  Double Insulation
-  Dust Collection
-  Carrying Case

	HS7010	HS7610	HS7611
<b>Continuous rating input</b>	1,600W	1,600W	1,600W
<b>Blade Diameter</b>	185 / 190 mm (7-1/4" / 7-1/2")	185 / 190 mm (7-1/4" / 7-1/2")	185 / 190 mm (7-1/4" / 7-1/2")
<b>Max Cutting Capacity</b>	90°: 65 / 67 mm (2-9/16" / 2-5/8") 45°: 44 / 45 mm (1-3/4" / 1-3/4")	90°: 63 / 65 mm (2-1/2" / 2-9/16") 45°: 44 / 45 mm (1-3/4" / 1-3/4")	90°: 63 / 65 mm (2-1/2" / 2-9/16") 45°: 44 / 45 mm (1-3/4" / 1-3/4")
<b>No Load Speed (RPM)</b>	5,500	5,500	5,500
<b>Dimensions (L x W x H)</b>	300x240x261 mm (11-3/4"x9-1/2"x10-1/4")	311x242x261 mm (12-1/4"x9-1/2"x10-1/4")	311x240x261 mm (12-1/4"x9-1/2"x10-1/4")
<b>Net weight</b>	4.0 kg (8.9 lbs)	3.9 kg (8.7 lbs)	3.9 kg (8.7 lbs)
<b>Power supply cord</b>	2.5 m (8.2 ft)	2.5 m (8.2 ft)	2.5 m (8.2 ft)

**Standard Equipment:** TCT Saw Blade, Rip Fence (Guide Rule), Hex Wrench, Dust Nozzle (country-specific)



# Circular Saw HS7010 / HS7610 / HS7611

185 mm (7-1/4") - 190 mm (7-1/2")



**Powerful 1,600 W motor delivers high power and performance**

Steel plate base  
One-finger switch

**HS7010**



Aluminum plate base  
One-finger switch

**HS7610**



Aluminum plate base  
Two-finger switch

**HS7611**

