






LN12N DM 170/12W

PHÂN BỐ QUANG




LƯỚI ĐỘ RƠI





LN12N DM 170x170/12W

PHÂN BỐ QUANG




LƯỚI ĐỘ RƠI




Model	Công suất	Dải điện áp hoạt động	Tần số	Quang thông	Nhiệt độ màu	Chỉ số hoàn màu	Tuổi thọ	Kích thước
LN12N DM 170/12W	12	150÷250	50	900/810/900	6500/3000/4000	80	25,000	160x41
LN12N DM 170x170/12W	12	150÷250	50	900/810/900	6500/3000/4000	80	25,000	160x160x41

BỘ ĐÈN M26 ĐỔI MÀU





M26 DM 1200/40W


PHÂN BỐ QUANG



LƯỚI ĐỘ RƠI




BỘ ĐÈN M36 ĐỔI MÀU





M36 DM 1200/40W

PHÂN BỐ QUANG



LƯỚI ĐỘ RƠI



Model	Công suất	Dải điện áp hoạt động	Tần số	Hệ số công suất	Hiệu suất sáng	Quang thông	Nhiệt độ màu	Chỉ số hoàn màu	Tuổi thọ	Kích thước
M26 DM 1200/40W	40	150÷250	50	0.5	117/130	4400/3960/4400	6500/3000/4000	80	25000	1200x75x25
M36 DM 1200/40W	40	150÷250	50	0.5	100/110	4400/4000/4400	6500/3000/4000	80	30000	1.172x61x31