



To cycle through between different color temperature, toggle light switch from on-off-on within 3 seconds.



LED



LED CEILING LIGHT Series (CCT version)



PLCA



PLCK



PLCQ

Ceiling light utilize high quality LED chips. With its high color rendering index (CRI ≥ 80), it is able to illuminate the true colors of an object. Energy efficient, long lifespan and environmentally friendly.

≥ 0.5	80Ra	IP20	25,000 Hours	AC220 240V	50-60Hz
Power factor	CRI	Protection grade	Lifespan	Voltage	Frequency

Outstanding features



Bridgelux/Epistar



3000K(Warm white) / 4200K(Neutral white) / 6500K(Cool daylight)



Compatible with Emergency Backup Battery



No UV radiation



Flicker-free



Low glare



Energy saving



High color rendering

SPECIFICATION AND PRICE

Model	PLCA295L12/CCT	PLCA355L18/CCT	PLCQ355L18/CCT	PLCK370L18/CCT
LED chip	Bridgelux/Epistar			
Wattage (W)	12W	18W	18W	18W
Efficacy (Lm/W)	85	85	85	85
Lumen (Lm)	1020	1530	1530	1530
Color temperature (K)	3000/4200/6500			
Dimensions (mm)	295	355	355	370x370
Installation	Surface			
Unit price (USD)	\$21.57	\$26.22	\$26.22	\$27.26

Suggested installation areas



Apartment



Supermarket



Retail Store



Office



Hotel



School



Hospital