




To cycle through between different color temperature, toggle light switch from on-off-on within 3 seconds.



LED



LED RECESSED DOWNLIGHT PRDYY Series



Note:

- Published lumen is total luminous flux of luminaire
- PF ≥ 0.5
- Lifespan: 25,000 hours
- CRI ≥ 80

≥ 0.5	80Ra	IP20	25,000 Hours	AC100 240V	50-60Hz
Power factor	CRI	Protection grade	Lifespan	Voltage	Frequency

Outstanding features

- Bridgelux/Samsung
- High quality PC diffuser cover
- 3000K(Warm white) / 4200K(Neutral white) / 6500K(Cool daylight)
- Compatible with Emergency Backup Battery
- Flicker-free
- High quality material and exceptional energy saving performance
- No UV radiation
- Low glare

SPECIFICATION AND PRICE

(Luminaire is able to emit different color temperature when toggling switch from On-Off-On)

Model	PRDYY108L5/CCT	PRDYY118L7/CCT	PRDYY138L9/CCT	PRDYY178L12/CCT	PRDYY188L20/CCT
LED chip	Bridgelux/Samsung				
Wattage (W)	5W	7W	9W	12W	20W
Efficacy (Lm/W)	85	95	100	110	110
Lumen (Lm)	425	665	900	1320	2200
Color temperature (K)	3000/4200/6500				
Dimensions (mm) (WxH)	108x32	118x32	138x32	178x36	188x36
Ceiling cut-out (mm)	90	90	115	155	160
Unit price (USD)	\$13.09	\$14.17	\$15.70	\$20.26	\$40.52

Suggested installation areas



Apartment



Supermarket



Retail Store



Office



Hotel



School



Hospital