


# COMBINATION DISPLAY LIGHT

## CDN series

NEW

### Specification

Model	CDN		
Appearance			
Power Voltage	24 V a.c. 50/60 Hz or 24 V d.c.	110 V a.c.	220 V a.c.
LED Indication Color	Red, green, yellow, white, orange, blue		
Insulation resistance	100 MΩ or more		
Voltage withstand	2,000 V a.c. 1 minute		
Power consumption	20 mA 0.4 VA	0.4 W	0.5 W
LED Rated Voltage	24 V d.c.		
Life	50,000 hours (24 V d.c., 25 °C)		
Ambient temperature and humidity	-20 °C ~ 40 °C, 45 ~ 85 % RH (Without condensation)		
Storage temperature	-25 ~ 55 °C		


(Note) CDN-S□ (30 X 30 mm) / CDN-R□ (30 X 40 mm)

### Suffix code

Model	Code				Content	
CDN-	□	□	-□□	□□	-□□□□□□	Set Indicator
Basic model name	S					Square (30×30 mm)
	R					Rectangle(30×40 mm)
Power Voltage	D2					24 V a.c. 50/60 Hz or 24 V d.c.
	A1					110 V a.c.
	A2					220 V a.c.
Collective Face Configuration Group		01				1st to 10th
Collective Face Configuration Column			01			Rows 1 to 20
Lamp color					C	C : COLOR color combination R (Red), G (Green), Y (Yellow), O (Orange), A (Blue), W (White)

## CR40 series

### Specifications

Model	CR40		
Appearance			
Power Voltage	100-240 V a.c.	380 V a.c.	12-24 V a.c./d.c.
Power consumption/current	4.4 VA or less	2.7 VA or less	18 mA or less
Display color	Red, green, yellow, blue, white		
Light source life	100,000 h		

### Suffix code

Model	Code	Content	
CR40	□ □	LED light source rectangular indicator	
Power Voltage	A0	100-240 V a.c.	LED (Condenser voltage drop type)
	A3	380 V a.c.	
	D0	12-24 V a.c./d.c.	LED (Resistance voltage drop type)
Display color	R	Red, green, yellow, blue, white	