


BL+ MOTOR + 18V + 18V → 36V



Tool-less chain adjustment type

Accessories

Guide Bar / Saw Chain / Guide Bar Cover



Guide Bar		Saw Chain						Bar Cover	File diameter		Drive Sprocket	
Bar length	Part No.	No. of drive links	gauge	pitch	Cutter type	Saw Chain Part No.	Bar Cover Part No.	1st half of top plate	2nd half of top plate	pitch/ No. of teeth	Part No.	
25cm/10"	168407-7	60	1.3mm/.050"	1/4"	25AP	MC	194098-8	452093-7	4.0mm	4.0mm	1/4" / 9	198259-2
30cm/12"	165245-8	46	1.1mm/.043"	3/8"	90PX	CC	196740-7	419288-5	4.5mm	4.0mm	3/8" / 6	221464-7
30cm/12"	165200-0	46	1.3mm/.050"	3/8"	91PX	CC	196211-4	419288-5	4.0mm	4.0mm	3/8" / 6	221464-7
35cm/14"	165246-6	52	1.1mm/.043"	3/8"	90PX	CC	196741-5	419288-5	4.5mm	4.0mm	3/8" / 6	221464-7
35cm/14"	165201-8	52	1.3mm/.050"	3/8"	91PX	CC	196212-2	419288-5	4.0mm	4.0mm	3/8" / 6	221464-7
40cm/16"	165247-4	56	1.1mm/.043"	3/8"	90PX	CC	196742-3	419242-9	4.5mm	4.0mm	3/8" / 6	221464-7
40cm/16"	165202-6	56	1.3mm/.050"	3/8"	91PX	CC	196213-0	419242-9	4.0mm	4.0mm	3/8" / 6	221464-7

Depth gauge jointer, File handle & Flat file



Depth gauge jointer	File handle	Flat file
Part No.	Part No.	Part No.
953 100 090	953 004 010	953 003 060

Chain oil & BIOTOP Chain oil



Chain oil		BIOTOP Chain oil	
Size	Part No.	Size	Part No.
100ml	182229-1	1L	980 008 610
1L	988 002 656	5L	980 008 611
5L	988 002 658		

File and File holder



Size	Saw chain type	File	File and File holder
		Part No.	Part No.
4mm	25AP, 91PX, 91VLX	953 003 090	953 030 010
4.5mm	90PX	953 003 100	953 030 020

Cordless Chain Saw

DUC353
350 mm (14")

Guide Bar Length DUC353: 350 mm (14")
Chain Pitch / Chain Gauge 9.5 mm (3/8") / 1.1 / 1.3 mm (.043" / .050")
Chain Speed 0 - 20 m/s (0 - 1,200 m/min)
Chain Oil Tank Volume 200 mL
Sound Pressure Level 87.7 dB(A)
Sound Power Level 98.7 dB(A)
Vibration Level Cutting Wood: 5.3 m/s²
Dimensions (L x W x H) DUC353: 762x215x235mm (30"x8-1/2"x9-1/4")
Net weight DUC353: 4.7 kg (10.4 lbs) - 5.4kg (11.8lbs)

- Variable Speed
 - Automatic Oiling
 - Chain Brake
 - Constant Speed
- Standard Equipment:**
Guide bar 350mm (165246-6), chain cover (419288-5), saw chain (196741-5).

The weight may differ depending on the attachment(s), including the battery cartridge. The lightest and heaviest combination, according to EPTA-Procedure 01/2014, are shown in the table. Items of standard equipment and specifications may vary by country or area.

M4-052023-1



Cordless Chain Saw

DUC353

Tool-less chain adjustment type

350mm (14")

Satisfy Professional's Needs



High Power & High Speed

High efficiency equivalent to 30mL class engine chain saws



CORDLESS CHAIN SAW for PROFESSIONAL



Outer Rotor Brushless Motor direct-drive



18V + 18V → 36V

CÔNG TY TNHH MAKITA VIỆT NAM

Kho 5/5, Block 16, 19L1-2 Đường số 3, KCN VSPP, P. Hòa Phú, TP. Thủ Đức, Bình Dương
ĐT: 0274 362 8338 - Fax: 0274 362 8339 - Website: www.makita.com.vn

CHI NHÁNH CTY TNHH MAKITA VN TẠI MIỀN BẮC
Khu 5, Số 1, Đường Số 6, KCN - BT - DV VSPP Bắc Ninh, P. Phú Châu, TP. Từ Sơn, T. Bắc Ninh
ĐT: 0222 376 5942 Fax: 0222 376 5941

TRUNG TÂM DỊCH VỤ KHÁCH HÀNG
CHI NHÁNH HÀ NỘI
65 Trường Chinh, P. Phương Liệt, Q. Thanh Xuân, TP. Hà Nội
ĐT: 0243 202 2585

TRUNG TÂM DỊCH VỤ KHÁCH HÀNG
CHI NHÁNH ĐÀ NẴNG
102 Triều Nữ Vương, P. Hải Châu 2, Q. Hải Châu, TP. Đà Nẵng
ĐT: 0236 352 5079 / 0236 352 5179 Fax: 0236 352 5478

TRUNG TÂM DỊCH VỤ KHÁCH HÀNG
CHI NHÁNH CẦN THƠ
366 Võ Văn Kiệt, Khu Vực 5, P. An Thới, Q. Bình Thủy, TP. Cần Thơ
ĐT: 0292 389 4358 Fax: 0292 389 4358

TRUNG TÂM DỊCH VỤ KHÁCH HÀNG
CHI NHÁNH BUỒN MA THUẬT
88 Lê Đức Thọ, P. Thới Mỹ, TP. Buon Ma Thuột, T. Đắk Lắk
ĐT: 0262 355 4550 Fax: 0262 355 4557

TRUNG TÂM DỊCH VỤ KHÁCH HÀNG
CHI NHÁNH HẢI PHÒNG
Số 01 Lê Đức Thọ, Di An Hoàng Hai Riverside, P. Thượng Lý, Q. Hồng Bàng, TP. Hải Phòng
ĐT: 0225 883 1529

TRUNG TÂM DỊCH VỤ KHÁCH HÀNG
CHI NHÁNH NHA TRANG
Lô 56-38 đường B6, Khu đô thị Vinh Diễm Trung, Xã Vinh Ngọc, TP. Nha Trang, T. Khánh Hòa
ĐT: 0258 220 0039

TRUNG TÂM DỊCH VỤ KHÁCH HÀNG
CHI NHÁNH HỒ CHÍ MINH
Số 12 Trịnh Văn Cấn, P. Cầu Ông Lãnh, Q. 1, TP. Hồ Chí Minh
ĐT: 0283 821 5191



Excellent cutting performance equivalent to 30mL class engine chain saws

High operating efficiency

Outer Rotor Brushless Motor direct-drive system provides high operating efficiency.



High operability

Chain brake and Variable speed trigger switch provide high operability equivalent to engine chain saws.

Powered by two 18V Li-ion batteries in series



SLIM & COMPACT BODY



Constant speed control

- minimizes reduction in rotation speed under load, keeping operation efficiency.
- Lowers noise under no load.

Metal spike bar




Metal chain catcher



Captive nuts prevent loss of nuts

DUC305 / DUC355 / DUC405
when removing a sprocket cover to replace a guide bar or a saw chain.



Chain tensioning screw

Tool-less chain adjustment

DUC303 / DUC353 / DUC400
Extendable lever

1. allows for:
 - Easier saw chain tightening
 - Higher tightening torque
2. can be quickly retracted at any angle.
3. reduces the area projecting from Sprocket cover.



Dial for easier saw chain tension adjustment

Variable speed trigger switch



Battery capacity warning lamp



Adjustable automatic chain lubrication



Chain oil level window

