

Depth gauge

can be adjusted for desired drilling depth simply by pushing single push button

Max Bit length

165 mm


(with DX05)

Dust collection inlet

can be adjusted according to bit length simply by pushing single push button

Filter cleaning mechanism **HEPA filter**

by turning the dial, the dust falls off from the filter



Large dust box cover

can be opened simply by pushing single push button for easy dust cleaning.



AVT

Anti Vibration Technology

XPT

EXTREME PROTECTION TECHNOLOGY

Twin LED job light

18V

LITHIUM-ION

BL

MOTOR



Excellent drilling performance

- Concrete with compressive strength of 40N/mm²
- Diameter : Ø10.5mm(3/8"), depth of 60mm(2-3/8")

Work Speed

About **70 % UP**

compared to our predecessor model

Work Volume

About **30 % UP**

compared to our predecessor model

Work Amount

About **80 pcs.**

Battery: BL1850B

AWS

Auto - start Wireless System

Wireless Unit

(option)

198901-5,
198900-7(EU),
199393-1(Asia)



Switch on the
tool



Vacuum cleaner
is activated



Accessories

Dust collection system

DX05



Dust cup

Part No.
198362-9

use with Grip base set
Part No.
194581-5



Dust case

Part No.
199595-9



HEPA Filter

Part No.
199596-7



Cordless Combination Hammer

- Variable Speed
- Brake
- Reversing
- SDS-PLUS Shank
- Torque Limiter

- Constant Speed
- Dust Collection
- Built-in Job Light
- Carrying Case

DHR182RTI: 2 battery BL1850B set, DC18RC fast charger (connector plastic case (type4) (821552-6))
DHR182Z: No battery, charger

Standard Equipment :
grip 36 complete (158057-6),
depth gauge (415486-9)
(no include bit).

DHR182 18 mm (11/16") Adapted for SDS-PLUS bits

Impact Energy	EPTA-Procedure 05/2009: 1.7 J Our experimental conditions: 1.6 J
Capacity	Concrete: 18 mm (11/16") Core Bit: 35 mm (1-3/8") Diamond Core Bit (Dry Type): 32 mm (1-1/4") Steel: 13 mm (1/2") Wood: 24 mm (15/16")
Blows Per Minute (BPM)	0 - 5,000
No Load Speed (RPM)	0 - 1,350
Max Output	450 W
Vibration Level	Hammer Drilling into Concrete: 11.0 m/s ² Drilling Into Metal: 2.5 m/s ² or less
Sound pressure Level	89 dB(A)
Sound power Level	100 dB(A)
Dimensions (L x W x H)	w/ BL1830B / BL1840B / BL1850B / BL1860B: 301x82x285 mm
Net weight	2.4 - 3.2 kg

The weight may differ depending on the attachment(s), including the battery cartridge. The lightest and heaviest combination, according to EPTA-Procedure 01/2014, are shown in the table. Items of standard equipment and specifications may vary by country or area.

CÔNG TY TNHH MAKITA VIỆT NAM

Kho 4-5-6, Block 16, 18L1-2 Đường số 3, KCN VSIP II, P. Hòa Phú,
TP. Thủ Đức, Bình Dương
ĐT: 0274 362 8338 - Fax: 0274 362 8339 - Website: www.makita.com.vn

CHI NHÁNH CTY TNHH MAKITA VN TẠI MIỀN BẮC

Kho 5, số 1, đường số 6, KCN - ĐT - DV VSIP Bắc Ninh, X. Phú Chấn,
TX. Từ Sơn, T. Bắc Ninh
ĐT: 0222 376 5942 Fax: 0222 376 5941

TRUNG TÂM DỊCH VỤ KHÁCH HÀNG

CHI NHÁNH ĐÀ NẴNG

102 Triệu Nữ Vương, P. Hải Châu 2, Q. Hải Châu, TP. Đà Nẵng
ĐT: 0236 352 5079 / 0236 352 5179 Fax: 0236 352 5479

TRUNG TÂM DỊCH VỤ KHÁCH HÀNG

CHI NHÁNH CẦN THƠ

226 Võ Văn Kiệt, P. An Thới, Q. Bình Thủy, TP. Cần Thơ
ĐT: 0292-3894358 Fax: 0292-3894359

TRUNG TÂM DỊCH VỤ KHÁCH HÀNG

CHI NHÁNH BUỒN MA THUỘT

60 Y Jút, P. Thới Nhất, TP. Buon Ma Thuột, T. Đắk Lắk
ĐT: 0262 355 4556 Fax: 0262 355 4557

TRUNG TÂM DỊCH VỤ KHÁCH HÀNG

CHI NHÁNH HẢI PHÒNG

Số 15, Phố Phạm Hồng Thái, Q. Hồng Bàng, TP. Hải Phòng
Điện thoại: 0225 8831 529

TRUNG TÂM DỊCH VỤ KHÁCH HÀNG

CHI NHÁNH NHA TRANG

1053 Đường 2 tháng 4, P. Vạn Thạnh, TP. Nha Trang, T. Khánh Hòa
ĐT: 0258 3823 338

TRUNG TÂM DỊCH VỤ KHÁCH HÀNG

CHI NHÁNH HỒ CHÍ MINH

Số 12 Trích Văn Cẩn, P. Cầu Ông Lãnh, Q. 1, TP. Hồ Chí Minh
Điện thoại: 028 3821 5191



Cordless Combination Hammer DHR182 18 mm (11/16") Adapted for SDS-PLUS bits



Adapted for
SDS-PLUS bits

The Lightest Combination Hammer with Dust Collection system

as of Feb. 2019

3.6 kg

(with DX05, BL1850B)




Hammering
with
Rotation

3

mode



Hammering



Rotation



HEPA filter

