# LOW TORQUE DC-TYPE AUTOMATIC TRIGGER START CLUTCH TYPE SERIES




SKD-2000 Series [SKD-2000L, SKD-2200L, SKD-2300L]




- New technology, ergonomic two-color housings, high temperature-resistant, vibration-resistant, friendly holder, fashionable appearance, light, good operation, free from fatigue under long-time using.
- Low torque 0.2kgf.cm within accuracy ±3%.
- Small, light body 270g. specially design for the precise needing of tiny screws.
- High tech DC motor with parts made in JAPAN with high-quality extra strong magnet, low electric current, stable running, high stability and automatically stop as the screw fastened.
- 0-8 stepless torque adjustment, rotation speed selected by switches. Hi & Lo.
- Best for industry of cell phones, digital cameras, notebook computers, PDA, DVD, MP3, CD-R, LCD and high-tech computer peripheral.
- Torque fixing ring (KC-4) can be set to fix torque. Slow start is optional for necessity.
- SKD-2000L Trigger series meet UL,CE approval and ESD is offered for the needs of customer.

### **External Dimension**



## **Torque Range Chart**



## **Specifications**

Model		SKD-2000L	SKD-2200L	SKD-2300L
Input Voltage		DC24V or DC32V		
Power Consumption		25W		
Torque	(kgf.cm)	0.2~3.5	0.5~7	1~10
	(Lbf.in)	0.18~3.01	0.44~6.10	0.89~8.67
	(N.m)	0.02~0.34	0.05~0.69	0.1~0.98
Repeatable Torque Accuracy(%)		±3%		
Torque Adjustment		Stepless		
Free Speed (r.p.m)	HI	1000	1000	700
	LO	700	700	500
Screw Size Dia (mm)	Machine Screw	1.0~2.3	1.4~2.6	1.6~3.0
	Tapping Screw	1.0~2.0	1.4~2.3	1.6~2.6
Weight(g)		270		
Length(mm)		LC/213 LB/222		
ESD(Anti-Static)		✓ (with black housing)		
CE		V		
RoHS		<b>v</b>		
Power Controller		SKP-32HL-60W		
Bit Type		B	C -	0 15.3 0 4 10-

### **Accessories**









