

Product datasheet

Specifications



electronic overcurrent relay - 0.5..60 A - 100..240 V AC/DC

EOCR3EZ-WRCZ7A

⚠ Discontinued on: Aug 20, 2023

⚠ End-of-service on: Jan 27, 2024

⚠ Discontinued

Main

Range Of Product	EOCR
Device Short Name	EOCR-3D420
Product Or Component Type	Protection relay
Protection Type	Overload, $I_n > OC$ setting Sensitivity to phase loss Sensitivity to phase reverse Locked rotor, $I_n > 3$ times OC setting Phase unbalance, 50 %
Product Specific Application	Overcurrent protection
Analogue Output Range	4...20 mA
Network Type	AC
Network Frequency	50...60 Hz
Protection Adjustment Range	0.5...10 A
Tripping Threshold	0.5...6 A

Complementary

[Us] Rated Supply Voltage	100...240 V AC/DC
Mounting Support	35 mm DIN rail Panel
Contacts Type And Composition	1 NO + 1 NC (OL)
Short-Circuit And Overload Protection	By 4 A gG fuse
[Ue] Rated Operational Voltage	600 V AC 50...60 Hz for power circuit conforming to UL 690 V AC 50...60 Hz for power circuit conforming to CSA 690 V AC 50...60 Hz for power circuit conforming to IEC 60947-4-1
[Uimp] Rated Impulse Withstand Voltage	6 kV conforming to IEC 60947-4-1
Reset	Manual reset Electrical 0...1 s by interruption of power supply
Time Delay Type	O-Time: 0.3, 1...30 s, off (definite) D-Time: 1...120 s, off (definite) O-Time: 1...30 class (inverse) D-Time: 0...120 s (inverse)
Display Type	7 segments LED
Power Consumption Per Relay	3 W
Connections - Terminals	Control circuit: cable 2 x 1...1.5 mm ² flexible with cable end - M3 Control circuit: cable 2 x 1...1.5 mm ² flexible without cable end - M3 Control circuit: cable 1 x 1...2.5 mm ² flexible with cable end - M3 Control circuit: cable 1 x 1...2.5 mm ² flexible without cable end - M3

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Tightening Torque	Control circuit: 0.8...1.2 N.m on cable, 4.7 mm
Height	71 mm
Width	70 mm
Depth	68 mm
Net Weight	0.325 kg

Environment

Standards	IEC 60947-4-1
Ip Degree Of Protection	IP20 conforming to IEC 60529
Ambient Air Temperature For Operation	-20...60 °C conforming to IEC 60947-4-1
Ambient Air Temperature For Storage	-30...80 °C
Operating Altitude	2000 m
Fire Resistance	650 °C conforming to IEC 60695-2-12 960 °C conforming to UL 94
Shock Resistance	15 gn for 11 ms conforming to IEC 60068-2-7
Vibration Resistance	4 gn on panel mounting conforming to IEC 60068-2-6 2 gn on 35 mm DIN rail conforming to IEC 60068-2-6
Dielectric Strength	2 kV 50...60 Hz in between case and circuit conforming to IEC 60255-5 1 kV 50...60 Hz in between contact conforming to IEC 60255-5 2 kV 50...60 Hz in between circuit conforming to IEC 60255-5
Surge Withstand	6 kV conforming to IEC 61000-4-5
Electromagnetic Compatibility	Resistance to radiated electromagnetic fields: 10 V/m level 3 conforming to IEC 61000-4-3 Resistance to electrostatic discharge: 8 kV air, 6 kV contact conforming to IEC 61000-4-2 Resistance to fast transient: 2 kV conforming to IEC 61000-4-4 Conducted RF disturbances: 10 V conforming to EN 61000-4-6 Conducted RF disturbances: class A conforming to EN 55011
[Ith] Conventional Free Air Thermal Current	5 A for control circuit
Permissible Current	250 V, 5 A AC

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	10.2 cm
Package 1 Width	8.3 cm
Package 1 Length	9.3 cm
Package 1 Weight	251.1 g

Sustainability


Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.


Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)

Well-being performance

 Mercury Free

 Rohs Exemption Information [Yes](#)

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive Compliant with Exemptions

China Rohs Regulation [China RoHS declaration](#)
Product out of China RoHS scope. Substance declaration for your information

Weee The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins