



SIMATIC ET 200SP, F-TM Count 1x1Vpp sin/cos HF, PROFIsafe, 1 channel, for incremental rotary encoders, sin/cos 1 Vpp, suitable for BU type A0, pack quantity: 1 unit

General information	
Product type designation	F-TM Count 1x1Vpp sin/cos HF
Firmware version	V1.0
<ul style="list-style-type: none"> <li>FW update possible</li> </ul>	Yes
usable BaseUnits	BU type A0
Color code for module-specific color identification plate	CC01
Product function	
<ul style="list-style-type: none"> <li>I&amp;M data</li> </ul>	Yes; I&M0 to I&M3
Engineering with	
<ul style="list-style-type: none"> <li>STEP 7 TIA Portal configurable/integrated from version</li> </ul>	Step 7 V17 or higher: use GSDML for prior versions
Supply voltage	
Rated value (DC)	24 V
power supply according to NEC Class 2 required	No
Load voltage L+	
<ul style="list-style-type: none"> <li>Rated value (DC)</li> <li>permissible range, lower limit (DC)</li> <li>permissible range, upper limit (DC)</li> <li>Reverse polarity protection</li> </ul>	24 V 20.4 V 28.8 V Yes
Input current	
Current consumption, max.	50 mA; without load, 150 mA with 300 mA encoder load
Encoder supply	
5 V encoder supply	
<ul style="list-style-type: none"> <li>5 V</li> <li>Short-circuit protection</li> <li>Output current, max.</li> </ul>	Yes; 5.1 V $\pm$ 3.5 % Yes; Electronic overload protection; no protection on applying a normal or counter voltage. 300 mA
Power loss	
Power loss, typ.	1.25 W
Address area	
Address space per module	
<ul style="list-style-type: none"> <li>Inputs</li> <li>Outputs</li> </ul>	14 byte; S7-300/400F CPU, 13 byte 5 byte; S7-300/400F CPU, 4 byte
Hardware configuration	
Automatic encoding	Yes
<ul style="list-style-type: none"> <li>Electronic coding element type H</li> </ul>	Yes
Digital inputs	
Number of digital inputs	1; (counter input)
Digital inputs, parameterizable	Yes
Digital input functions, parameterizable	
<ul style="list-style-type: none"> <li>Gate start/stop</li> </ul>	Yes

<ul style="list-style-type: none"> <li>Counter for incremental encoder</li> <li>— Number, max.</li> </ul>	Yes 1
<b>Input voltage</b>	
<ul style="list-style-type: none"> <li>Type of input voltage</li> </ul>	sin/cos 1 Vpp
<b>Input delay (for rated value of input voltage)</b>	
<ul style="list-style-type: none"> <li>Minimum pulse width for program reactions</li> </ul>	2.5 µs for parameterization "none"
<b>for technological functions</b>	
<ul style="list-style-type: none"> <li>— parameterizable</li> </ul>	Yes
<b>Cable length</b>	
<ul style="list-style-type: none"> <li>shielded, max.</li> </ul>	150 m
<b>Encoder</b>	
<b>Connectable encoders</b>	
<ul style="list-style-type: none"> <li>Incremental encoder (symmetrical)</li> </ul>	Yes; up to 200 kHz depending on cable type and length
<b>Encoder signals, incremental encoder (symmetrical)</b>	
<ul style="list-style-type: none"> <li>Input voltage</li> <li>Input frequency, max.</li> <li>Counting frequency, max.</li> <li>Cable length, shielded, max.</li> <li>Incremental encoder with A/B tracks, 90° phase offset</li> <li>Incremental encoder with A/B tracks, 90° phase offset and zero track</li> </ul>	1 Vpp, centered at 2.5 V offset 200 kHz 800 kHz; with quadruple evaluation 150 m Yes; sin/cos Yes; sin/cos/zero
<b>Interrupts/diagnostics/status information</b>	
<b>Diagnostics function</b>	Yes; see chapter "Diagnostic Messages" in the manual
<b>Alarms</b>	
<ul style="list-style-type: none"> <li>Diagnostic alarm</li> <li>Hardware interrupt</li> </ul>	Yes No
<b>Diagnoses</b>	
<ul style="list-style-type: none"> <li>Monitoring the supply voltage</li> <li>Wire-break</li> <li>Short-circuit</li> <li>A/B transition error at incremental encoder</li> </ul>	Yes Yes Yes Yes
<b>Diagnostics indication LED</b>	
<ul style="list-style-type: none"> <li>RUN LED</li> <li>ERROR LED</li> <li>Monitoring of the supply voltage (PWR-LED)</li> <li>Channel status display</li> <li>for channel diagnostics</li> <li>for module diagnostics</li> </ul>	Yes; green LED Yes; red LED Yes; green LED Yes; green LED Yes; red LED Yes; green/red DIAG LED
<b>Integrated Functions</b>	
<b>Counter</b>	
<ul style="list-style-type: none"> <li>Number of counters</li> <li>Counting frequency, max.</li> </ul>	Yes 1 800 kHz; with quadruple evaluation
<b>Safety monitoring functions</b>	
<ul style="list-style-type: none"> <li>Safe Operating Stop (SOS)</li> <li>Safely-Limited Speed (SLS)</li> <li>Safe Direction (SDI)</li> <li>Safe Speed Monitor (SSM)</li> </ul>	Yes Yes Yes Yes
<b>Counting functions</b>	
<ul style="list-style-type: none"> <li>Continuous counting</li> <li>Counter response parameterizable</li> <li>Software gate</li> <li>Counting range, parameterizable</li> </ul>	Yes Yes Yes Yes
<b>Measuring functions</b>	
<b>Measuring range</b>	
<ul style="list-style-type: none"> <li>— Frequency measurement, min.</li> <li>— Frequency measurement, max.</li> <li>— Cycle duration measurement, min.</li> <li>— Cycle duration measurement, max.</li> <li>— Velocity measurement, min.</li> <li>— Velocity measurement, max.</li> </ul>	0.04 Hz 800 kHz; with quadruple evaluation 1 µs 25 s 0 (speed in configured units per selected time basis - speed*1 000) 2 147 483 (speed in configured units per selected time basis - speed*1 000)
<b>Accuracy</b>	

— Frequency measurement	up to 100 ppm; depending on measuring interval and signal evaluation; at low frequency external noise may have an effect on accuracy (reference the graph in 2.2.3)
— Cycle duration measurement	up to 100 ppm; depending on measuring interval and signal evaluation; at low frequency external noise may have an effect on accuracy (reference the graph in 2.2.3)
— Velocity measurement	up to 100 ppm; depending on measuring interval and signal evaluation; at low frequency external noise may have an effect on accuracy (reference the graph in 2.2.3)

### Potential separation

Potential separation channels	
• between the channels	No; Only one channel is available
• between the channels and backplane bus	Yes
• Between the channels and load voltage L+	No
• between the channels and the power supply of the electronics	No

### Isolation

Isolation tested with	707 V DC (type test)
-----------------------	----------------------

### Standards, approvals, certificates

Suitable for safety functions	Yes
-------------------------------	-----

Ecological footprint	
• environmental product declaration	Yes

Global warming potential	
— global warming potential, (total) [CO2 eq]	88.3 kg
— global warming potential, (during production) [CO2 eq]	13.1 kg
— global warming potential, (during operation) [CO2 eq]	76.6 kg
— global warming potential, (after end of life cycle) [CO2 eq]	-1.37 kg

Highest safety class achievable in safety mode	
• Performance level according to ISO 13849-1	Cat. 4, PLe
• SIL acc. to IEC 61508	SIL 3

Probability of failure (for service life of 20 years and repair time of 100 hours)	
— low demand mode: PFDavg in accordance with SIL1	< 2.00E-03 signal monitoring disabled
— Low demand mode: PFDavg in accordance with SIL3	< 3.00E-05
— high demand/continuous mode: PFH in accordance with SIL1	< 3.00E-08 1/h signal monitoring disabled
— High demand/continuous mode: PFH in accordance with SIL3	< 1.00E-09 1/h

### Ambient conditions

Ambient temperature during operation	
• horizontal installation, min.	0 °C
• horizontal installation, max.	60 °C
• vertical installation, min.	0 °C
• vertical installation, max.	55 °C

Altitude during operation relating to sea level	
• Ambient air temperature-barometric pressure-altitude	On request: Installation altitudes greater than 2 000 m

### Dimensions

Width	15 mm
Height	73 mm
Depth	58 mm

### Weights

Weight, approx.	42 g
-----------------	------

### Classifications

	Version	Classification
eClass	14	27-24-26-05
eClass	12	27-24-26-05
eClass	9.1	27-24-26-05
eClass	9	27-24-26-05
eClass	8	27-24-26-05
eClass	7.1	27-24-26-05

eClass	6	27-24-26-05
ETIM	9	EC001601
ETIM	8	EC001601
ETIM	7	EC001601
IDEA	4	3567
UNSPSC	15	32-15-17-05

Approvals / Certificates

General Product Approval	For use in hazardous locations
--------------------------	--------------------------------



EG-Konf.



[Manufacturer Declaration](#)



UL



RCM

[EM](#)

For use in hazardous locations	Functional Safety	Marine / Shipping
--------------------------------	-------------------	-------------------



IECEX



ATEX

[CCC-Ex](#)



TUV

[Type Examination Certificate](#)



ABS

Marine / Shipping



BUREAU VERITAS



DNV



LRS

[NK / Nippon Kaiji Kyokai](#)



RINA

[CCS \(China Classification Society\)](#)

Marine / Shipping	Industrial Communication
-------------------	--------------------------



KR

[PROFIsafe](#)

last modified:

10/9/2024