

Female Pre-Insulating Joint Cable Shoes Terminals

Female Pre-Insulating Joint Cable Shoes Terminals

母预绝缘接头

FEMALE PRE-INSULATING JOINT

型号 Item No	接插规格 Connecting Spc.(mm)	材料厚度 Thickness (mm)	尺寸Dimension (mm)					颜色 Color
			B	D&	d&	L	H	

导线截面: 0.5~1.5mm² (美国线规22-16) 最大电流: I_{max}=10A 材料: 黄铜

Cable size: 0.5~1.5mm² (A.W.G.22-16) Max current: I_{max}=10A Material: copper

FDD1.25-110(5)	0.5 x 2.8	0.3	3.8	4.3	1.7	19.0	10.0	红 Red
FDD1.25-110(8)	0.8 x 2.8	0.3	3.8	4.3	1.7	19.0	10.0	
FDD1.25-187(5)	0.5 x 4.75	0.35	5.6	4.3	1.7	19.0	10.0	
FDD1.25-187(8)	0.8 x 4.75	0.35	5.6	4.3	1.7	19.0	10.0	
FDD1.25-205	0.5 x 5.2	0.35	6.5	4.3	1.7	20.0	10.0	
FDD1.25-250	0.8 x 6.35	0.4	7.4	4.3	1.7	21.0	10.0	

导线截面: 1.5~2.5mm² (美国线规16-14) 最大电流: I_{max}=15A 材料: 黄铜

Cable size: 1.5~2.5mm² (A.W.G.16-14) Max current: I_{max}=15A Material: copper

FDD2-110(5)	0.5 x 2.8	0.3	3.8	4.9	2.3	19.0	10.0	蓝 Blue
FDD2-110(8)	0.8 x 2.8	0.3	3.8	4.9	2.3	19.0	10.0	
FDD2-187(5)	0.5 x 4.75	0.35	5.6	4.9	2.3	19.0	10.0	
FDD2-187(8)	0.8 x 4.75	0.35	5.6	4.9	2.3	19.0	10.0	
FDD2-205	0.5 x 5.2	0.35	6.5	4.9	2.3	20.0	10.0	
FDD2-250	0.8 x 6.35	0.4	7.4	4.9	2.3	21.0	10.0	
FDD2-312	0.8 x 8.0	0.4	9.0	4.9	2.3	23.0	10.0	

导线截面: 4~6mm² (美国线规12-10) 最大电流: I_{max}=24A 材料: 黄铜

Cable size: 4~6mm² (A.W.G.12-10) Max current: I_{max}=24A Material: copper

FDD5.5-187(5)	0.5 x 4.75	0.4	5.6	6.7	3.4	23.0	13.0	黄 Yellow
FDD5.5-312	0.8 x 8.0	0.5	9.0	6.7	3.4	27.0	13.0	
FDD5.5-250	0.8 x 6.35	0.4	7.4	6.7	3.4	25.0	13.0	
FDD5.5-375	1.2 x 9.4	0.5	10.9	6.7	3.4	29.6	13.0	

