

## 22MM 2 MODE SDS PLUS HAMMER, 2 KGS (MADE IN INDIA)

### D25032B

|                                              |                                  |
|----------------------------------------------|----------------------------------|
| Power Input                                  | 710W                             |
| Max. Impact Energy                           | 2.1 J                            |
| Impact Energy (EPTA 05/2009)                 | 2.0 J                            |
| No Load Speed                                | 0-1550 rpm                       |
| Blows Per Minute                             | 0-5680 bpm                       |
| Optimum Drilling Capacity [Concrete]         | 4-12 mm                          |
| Max. Drilling Capacity [Concrete]            | 22 mm                            |
| Max. Drilling Capacity [Core bit/Wood/Metal] | 50/30/13 mm                      |
| Operation Mode                               | Rotation/Hammering with rotation |
| Weight                                       | 2.5 Kg                           |
| Length x Height                              | 330 x 210 mm                     |
| Vibration Level                              | 13.6 m/s <sup>2</sup>            |



**MADE IN INDIA**

## 22MM 3 MODE SDS PLUS HAMMER, 2 KGS (MADE IN INDIA)

### D25033K

|                                              |                                            |
|----------------------------------------------|--------------------------------------------|
| Power Input                                  | 710W                                       |
| Max. Impact Energy                           | 2.1 J                                      |
| Impact Energy (EPTA 05/2009)                 | 2.0 J                                      |
| No Load Speed                                | 0-1550 rpm                                 |
| Blows Per Minute                             | 0-5680 bpm                                 |
| Optimum Drilling Capacity [Concrete]         | 4-12 mm                                    |
| Max. Drilling Capacity [Concrete]            | 22 mm                                      |
| Max. Drilling Capacity [Core bit/Wood/Metal] | 50/30/13 mm                                |
| Operation Mode                               | Hammering/Rotation/Hammering with rotation |
| Weight                                       | 2.5 Kg                                     |
| Length x Height                              | 330 x 210 mm                               |
| Vibration Level                              | 13.6 m/s <sup>2</sup>                      |



**MADE IN INDIA**

## 26MM 3 MODE COMBINATION HAMMER, 2 KGS (MADE IN INDIA)

### D25133K

|                                              |                                            |
|----------------------------------------------|--------------------------------------------|
| Power Input                                  | 800W                                       |
| Max. Impact Energy                           | 2.8 J                                      |
| Impact Energy (EPTA 05/2009)                 | 2.6 J                                      |
| No Load Speed                                | 0-1500 rpm                                 |
| Blows Per Minute                             | 0-5500 bpm                                 |
| Optimum Drilling Capacity [Concrete]         | 4-14 mm                                    |
| Max. Drilling Capacity [Concrete]            | 26 mm                                      |
| Max. Drilling Capacity [Core bit/Wood/Metal] | 50/30/13 mm                                |
| Operation Mode                               | Hammering/Rotation/Hammering with rotation |
| Weight                                       | 2.6 Kg                                     |
| Length x Height                              | 335 x 210 mm                               |
| Vibration Level                              | 15.4 m/s <sup>2</sup>                      |



**MADE IN INDIA**

## 28MM 3 MODE SDS PLUS COMBINATION HAMMER, 2 KGS

### D25143K

|                                              |                                                |
|----------------------------------------------|------------------------------------------------|
| Power Input                                  | 900W                                           |
| Max. Impact Energy                           | 3.2 J                                          |
| Impact Energy (EPTA 05/2009)                 | 3.0 J                                          |
| No Load Speed                                | 0-1450 rpm                                     |
| Blows Per Minute                             | 0-5350 bpm                                     |
| Optimum Drilling Capacity [Concrete]         | 4-18 mm                                        |
| Max. Drilling Capacity [Concrete]            | 28 mm                                          |
| Max. Drilling Capacity [Core bit/Wood/Metal] | 65/30/13 mm                                    |
| Operation Mode                               | Hammering/Rotation/<br>Hammering with rotation |
| Weight                                       | 3.0 Kg                                         |
| Length x Height                              | 340 x 210 mm                                   |
| Vibration Level                              | 14.9 m/s <sup>2</sup>                          |



## 30MM 3 MODE SDS PLUS COMBINATION HAMMER, 3KGS

### D25333K

|                                              |                                                |
|----------------------------------------------|------------------------------------------------|
| Power Input                                  | 950W                                           |
| Max. Impact Energy                           | 4.2 J                                          |
| Impact Energy (EPTA 05/2009)                 | 3.5 J                                          |
| No Load Speed                                | 0-1150 rpm                                     |
| Blows Per Minute                             | 0-5200 bpm                                     |
| Optimum Drilling Capacity [Concrete]         | 6-20 mm                                        |
| Max. Drilling Capacity [Concrete]            | 30 mm                                          |
| Max. Drilling Capacity [Core bit/Wood/Metal] | 65/30/13 mm                                    |
| Operation Mode                               | Hammering/Rotation/<br>Hammering with rotation |
| Weight                                       | 3.7 Kg                                         |
| Length x Height                              | 355 x 250 mm                                   |
| Vibration Level                              | 6.9 m/s <sup>2</sup>                           |



## 32MM 3 MODE SDS PLUS COMBINATION HAMMER, 4KGS

### D25413K

|                                              |                                                |
|----------------------------------------------|------------------------------------------------|
| Power Input                                  | 1000W                                          |
| Max. Impact Energy                           | 4.9 J                                          |
| Impact Energy (EPTA 05/2009)                 | 4.2 J                                          |
| No Load Speed                                | 0-820 rpm                                      |
| Blows Per Minute                             | 0-4700 bpm                                     |
| Optimum Drilling Capacity [Concrete]         | 6-22 mm                                        |
| Max. Drilling Capacity [Concrete]            | 32 mm                                          |
| Max. Drilling Capacity [Core bit/Wood/Metal] | 100/32/13 mm                                   |
| Operation Mode                               | Hammering/Rotation/<br>Hammering with rotation |
| Weight                                       | 4.2 Kg                                         |
| Length x Height                              | 370 x 250 mm                                   |
| Vibration Level                              | 8.2 m/s <sup>2</sup>                           |



## 40MM SDS MAX COMBINATION HAMMER, 5 KGS

**D25481K**

|                                      |                                                |
|--------------------------------------|------------------------------------------------|
| Power Input                          | 1050W                                          |
| Max. Impact Energy                   | 7.3 J                                          |
| Impact Energy (EPTA 05/2009)         | 6.1 J                                          |
| No Load Speed                        | 540 rpm                                        |
| Blows Per Minute                     | 3150 bpm                                       |
| Optimum Drilling Capacity [Concrete] | 16-30 mm                                       |
| Max. Drilling Capacity [Concrete]    | 40 mm                                          |
| Max. Drilling Capacity [Core bit]    | 100 mm                                         |
| Operation Mode                       | Hammering/Rotation/<br>Hammering with rotation |
| Weight                               | 5.9 Kg                                         |
| Length x Height                      | 453 x 263 mm                                   |
| Vibration Level                      | 9.4 m/s <sup>2</sup>                           |



## 5KG SDS-MAX CHIPPING HAMMER

**D25810K**

|                              |                      |
|------------------------------|----------------------|
| Power Output                 | 1050W                |
| Max. Impact Energy           | 8.5 J                |
| Impact Energy (EPTA 05/2009) | 7.1 J                |
| Blows Per Minute             | 3150 bpm             |
| Chisel Positions             | 18                   |
| Weight                       | 5.6 Kg               |
| Length x Height              | 462 mm x 263 mm      |
| Vibration Level              | 8.5 m/s <sup>2</sup> |

