

CDN

High brightness LED set indicator

- 2 types of surface dimension : 30x30mm, 30x40mm
- Applied high brightness square surface LED unit
- 6 types of various indicating colors
- Simple assembling and able to change color on the spot
- Max 200 compositions (10 rows 20 columns)



Specification

Model	CDN		
Power supply voltage	24 V a.c. / d.c	110 V a.c.	220 V a.c.
LED rated voltage	24 V d.c.		
LED rated current	20 mA		
LED color	Red, Green, Yellow, White, Orange, Blue		
Insulation resistance	100 MΩ or more (500 V d.c.)		
Dielectric voltage	2,000 V a.c. 50 / 60 Hz for 1 minute		
Power consumption	0.4 VA	0.4 W	0.5 W
LED rated voltage	24 V d.c.		
LED life expectancy	50,000 hours (24 V d.c., 25 °C)		
Terminal	M3.5 screw tightening		
Terminal tightening torque	0.8 N·m or less		
Ambient temperature	-20 ~ 55 °C (provided there is no freezing or condensation)		
Ambient humidity	45 ~ 85 % RH		
Storage temperature	-40 ~ 70 °C		
Certification			

※ CDN-S□ (30 X 30 mm) / CDN-R□ (30 X 40 mm)