

Megapixel Fixed Focal Length Lenses Support 1.1"

Model	VS-HVA1226				
Focal Length (f)	12 mm				
Maximum Aperture Ratio	1: 2.6				
Aperture	F 2.6 ~ Close				
Angle of View (1.1")	45.6° × 60.0° (Diagonal: 70.8°)				
M.O.D	100 mm				
TV Distortion (1.1")	0.15 %				
Operation	Manual (Lock screw M2)				
Wavelength	Visible				
Mount	C-Mount				
Flange Back	17.526 mm				
Sensor Size (max.)	1.1"				
Filter Thread	M 34 P= 0.5				
Weight (approx.)	126 g				
Dimension	ϕ 37.5 (max.) × L = 51.2 mm				

Megapixel Fixed Focal Length Lenses Support 1.1"

Model	VS-HVA1626
Focal Length (f)	16 mm
Maximum Aperture Ratio	1: 2.6
Aperture	F 2.6 ~ Close
Angle of View (1.1")	35.1° × 46.8° (Diagonal: 56.3°)
M.O.D	100 mm
TV Distortion (1.1")	0.11 %
Operation	Manual (Lock screw M2)
Wavelength	Visible
Mount	C-Mount
Flange Back	17.526 mm
Sensor Size (max.)	1.1"
Filter Thread	M 30.5 P= 0.5
Weight (approx.)	128 g
Dimension	ϕ 37.5 (max.) × L = 50 mm

Megapixel Fixed Focal Length Lenses Support 1.1"

Model	VS-HVA2524
Focal Length (f)	25 mm
Maximum Aperture Ratio	1: 2.4
Aperture	F 2.4 ~ Close
Angle of View (1.1")	23.1° × 31.3° (Diagonal: 39.4°)
M.O.D	100 mm
TV Distortion (1.1")	-0.09 %
Operation	Manual (Lock screw M2)
Wavelength	Visible
Mount	C-Mount
Flange Back	17.526 mm
Sensor Size (max.)	1.1"
Filter Thread	M 35.5 P= 0.5
Weight (approx.)	116 g
Dimension	ϕ 37.5 (max.) × L = 45 mm

Megapixel Fixed Focal Length Lenses Support 1.1"

Model	VS-HVA3522				
Focal Length (f)	35 mm				
Maximum Aperture Ratio	1: 2.2				
Aperture	F	2.2	~	Close	
Angle of View (1.1″)	16.7°	×	22.7°	(Diagonal:28.7°)	
M.O.D	200 mm				
TV Distortion (1.1″)	0.03 %				
Operation	Manual (Lock screw M2)				
Wavelength	Visible				
Mount	C-Mount				
Flange Back	17.526 mm				
Sensor Size (max.)	1.1″				
Filter Thread	M	34	P=	0.5	
Weight (approx.)	122 g				
Dimension	φ	39.5	(max.)	×	L = 48.5 mm

Megapixel Fixed Focal Length Lenses Support 1.1"

Model	VS-HVA5024				
Focal Length (f)	50 mm				
Maximum Aperture Ratio	1: 2.4				
Aperture	F 2.4 ~ Close				
Angle of View (1.1")	12.0° × 16.4° (Diagonal: 20.3°)				
M.O.D	200 mm				
TV Distortion (1.1")	0.03 %				
Operation	Manual (Lock screw M2)				
Wavelength	Visible				
Mount	C-Mount				
Flange Back	17.526 mm				
Sensor Size (max.)	1.1"				
Filter Thread	M 30.5 P= 0.5				
Weight (approx.)	142 g				
Dimension	ϕ 40 (max.) × L = 57.5 mm				