



VF series Insulated RingTerminal is made of high-quality red copper material with tight contact, good conductivity, small resistivity and large load. Vinyl insulation material, high protection grade, tin-plated surface, anti-oxidation, prolong the anti-rust period.

• **INSULATION MATERIAL : VINYL**

Unit:mm

ITEM NO.	DIMENSIONS					WIRE RANGE		COLOR
	d2ø	B	L	H	Dø	mm ²	AWG	
VF1.25-3A	3.2	5.5	16.3	11.0	4.0	0.5~1.5	22~16	RED
VF1.25-3	3.7	5.5	16.3	11.0	4.0			
VF1.25-3M	3.7	6.6	17.6	11.0	4.0			
VF1.25-4	4.3	8.0	18.3	11.0	4.0			
VF1.25-4M	4.3	6.6	17.6	11.0	4.0			
VF1.25-5	5.3	8.0	18.3	11.0	4.0			
VF1.25-6	6.4	11.6	22.4	11.0	4.0			
VF1.25-8	8.4	13.6	30.0	11.0	4.0			
VF1.25-10	10.5	13.6	30.0	11.0	4.0			
VF2-3A	3.2	8.5	18.7	11.0	4.5	1.5~2.5	16~14	BLUE
VF2-3	3.7	8.5	18.7	11.0	4.5			
VF2-3M	3.7	6.6	17.3	11.0	4.5			
VF2-4	4.3	8.5	18.7	11.0	4.5			
VF2-4M	4.3	6.6	17.3	11.0	4.5			
VF2-5	5.3	9.5	18.2	11.0	4.5			
VF2-6	6.4	12.0	22.0	11.0	4.5			
VF2-8	8.4	12.0	22.0	11.0	4.5			
VF2-10	10.5	13.6	24.9	11.0	4.5			
VF5.5-3	3.7	9.5	26.3	13.7	6.3	4.0~6.0	12~10	YELLOW
VF5.5-4	4.3	9.5	26.3	13.7	6.3			
VF5.5-4S	4.3	7.2	22.0	12.5	6.5			
VF5.5-5	5.3	9.5	26.3	13.7	6.3			
VF5.5-6	6.4	11.0	28.0	13.7	6.3			
VF5.5-8	8.4	15.0	34.0	13.7	6.3			
VF5.5-10	10.5	15.0	34.0	13.7	6.3			
VF5.5-12	13.0	15.0	34.0	13.7	6.3			

VF14-4	4.3	12.0	41.0	22.5	10.5	16	6	BLUE
VF14-5	5.3	12.0	41.0	22.5	10.5			
VF14-6	6.4	12.0	41.0	22.5	10.5			
VF14-8	8.4	16.0	44.0	22.5	10.5			
VF14-10	10.5	16.0	44.5	22.5	10.5			
VF14-11	11.5	22.0	53.0	22.5	10.5			
VF14-12	13.0	22.0	53.0	22.5	10.5			
VF22-5S	5.3	12.0	45.0	24.0	13.0	25	4	YELLOW
VF22-5	6.4	12.0	45.0	24.0	13.0			
VF22-6S	8.4	12.0	45.0	24.0	13.0			
VF22-6	5.3	12.0	45.0	24.0	13.0			
VF22-8S	6.4	12.0	45.0	24.0	13.0			
VF22-8	8.4	16.5	45.0	24.0	13.0			
VF22-10S	10.5	16.5	45.0	24.0	13.0			
VF22-10	10.5	17.5	45.0	24.0	13.0			
VF22-11	11.5	22.0	54.0	24.0	13.0			
VF22-12	13.0	22.0	54.0	24.0	13.0			
VF38-6S	6.4	15.3	52.0	27.0	14.5	35	2	RED
VF38-6	8.4	15.3	52.0	27.0	14.5			
VF38-8S	10.5	15.3	52.0	27.0	14.5			
VF38-8	6.4	22.0	52.0	27.0	14.5			
VF38-10S	8.4	22.0	52.0	27.0	14.5			
VF38-10	10.5	22.0	52.0	27.0	14.5			
VF38-11	11.5	22.0	55.0	27.0	14.5			
VF38-12	13.0	22.0	55.0	27.0	14.5			