

Product variant	Switching output	Light spot size	Teach-in mode	Certificate
KT8L-N3756	NPN	Ø 3 mm	Static 2-point teach-in, Dynamic teach-in (min/max)	EU declaration of conformity, UK declaration of conformity, ACMA declaration of conformity, Moroccan declaration of conformity, China-RoHS, cULus certificate, Laser safety (IEC 60825-1) declaration of manufacturer
KT8L-N3656	NPN	Ø 0.3 mm	Static 2-point teach-in, Dynamic teach-in (min/max)	EU declaration of conformity, UK declaration of conformity, ACMA declaration of conformity, Moroccan declaration of conformity, China-RoHS, cULus certificate, Laser safety (IEC 60825-1) declaration of manufacturer
KT8L-P3756	PNP	Ø 3 mm	Static 2-point teach-in, Dynamic teach-in (min/max)	EU declaration of conformity, UK declaration of conformity, ACMA declaration of conformity, Moroccan declaration of conformity, China-RoHS, cULus certificate, Laser safety (IEC 60825-1) declaration of manufacturer
KT8L-P3656	PNP	Ø 0.3 mm	Static 2-point teach-in, Dynamic teach-in (min/max)	EU declaration of conformity, UK declaration of conformity, ACMA declaration of conformity, Moroccan declaration of conformity, China-RoHS, cULus certificate, Laser safety (IEC 60825-1) declaration of manufacturer