




LED RECESSED DOWNLIGHT PRDLL Series



Note:

- Published lumen is total luminous flux of luminaire
- PF ≥ 0.9
- Lifespan: 50,000 hours
- CRI ≥ 80

≥ 0.9	80Ra	IP20	50,000 Hours	AC100 240V	50-60Hz
Power factor	CRI	Protection grade	Lifespan	Voltage	Frequency

Outstanding features



Bridgelux/Epistar



High quality PC diffuser cover



3000K(Warm white) / 4200K(Neutral white) / 6500K(Cool daylight)



Adjustable brightness



Energy saving



Easy installation and maintenance



Available in different sizes



No mercury, environmentally friendly

SPECIFICATION AND PRICE (Compatible with Triac Dimmer)

Model	PRDLL110L7/D1	PRDLL139L12/D1	PRDLL180L20/D1	PRDLL230L35/D1
LED chip	Bridgelux/Epistar			
Wattage (W)	7W	12W	20W	35W
Efficacy (Lm/W)	90	95	101	125
Lumen (Lm)	630	1126	1970	4189
Color temperature (K)	3000/4200/6500			
Dimensions (mm) (WxH)	110x53	139x60	180x70	230x90
Ceiling cut-out (mm)	98	115	165	205
Unit price (USD)	\$31.26	\$48.96	\$70.91	\$95.04

Suggested installation areas



Apartment



Supermarket



Retail Store



Office



Hotel



School



Hospital

Adjustable brightness (Model code/D1 is compatible with triac dimmer only, compatibility with 1-10V dimmer and Dali dimmer are available upon request)