




LED RECESSED DOWNLIGHT PRDFF Series



Note:

- Published lumen is total luminous flux of luminaire
- PF ≥ 0.9
- Lifespan: 50,000 hours
- CRI ≥ 80

≥ 0.9	80Ra	IP20	50,000 Hours	AC100 240V	50-60Hz
Power factor	CRI	Protection grade	Lifespan	Voltage	Frequency

Outstanding features

- Bridgelux/Nichia
- High quality aluminium alloy heatsink
- 3000K(Warm white) / 4200K(Neutral white) / 6500K(Cool daylight)
- Energy saving
- Flicker-free
- Low glare
- No UV radiation
- Minimise blue light emission

SPECIFICATION AND PRICE

Model	PRDFF90L5	PRDFF90L5/D1
LED chip	Bridgelux/Nichia	
Wattage (W)	5W	5W
Efficacy (Lm/W)	90	90
Lumen (Lm)	450	450
Color temperature (K)	3000/4200/6500	
Dimensions (mm) <small>(WxH)</small>	90x57	90x57
Ceiling cut-out (mm)	75	75
Unit price (USD)	\$23.17	\$43.96

Suggested installation areas



Adjustable brightness (Model code/D1 is compatible with triac dimmer only, compatibility with 1-10V dimmer and Dali dimmer are available upon request)