


FOOT MASTER®

Leveling casters GD series








 **60~1,000kg**  **RoHS**  **-10~90°C**



Brackets: Pressed steel plate(100/120 series: forged steel), double ball bearing with hardened bearing seats in the swivel head, ivory-colored aluminum frame, height adjustment with integrated orange handle or spanner(120 series: only available for spanner), anti-vibration NBR pad (120 series: AL)

Surface Treatment: Powder coating, zinc plated

* Recommended Load = Load Cap. × 2

Swivel	Wheel type	 mm	 mm	 Kg	 mm	 mm	 mm	 mm
GD-40-S	NYN	42	20	60	71+10	30	M8x1,25P	10
GD-60-S		50	25	280	82+10	36	M12x1,75P M16x2,0P 1/2"-13UNC	18
GD-80-S		63	28	550	103+15	46	M12x1,75P 1/2"-13UNC	16
GD-100-S		75	30	800	120+12	53	M16x2,0P	24
GD-120-S		75	30	1,000	120+12	53		
GD-40-S	MCN	40	19	60	71+10	30	M8x1,25P	10
GD-60-S		49	25	280	82+10	36	M12x1,75P M16x2,0P 1/2"-13UNC	18
GD-80-S		62	28	550	103+15	46	M12x1,75P 1/2"-13UNC	16
GD-100-S		74	30	800	120+12	53	M16x2,0P	24
GD-120-S		74	30	1,000	120+12	53		
GD-60-S	HUP	50	25	280	82+10	36	M12x1,75P M16x2,0P 1/2"-13UNC	18
GD-80-S		63	28	550	103+15	46	M12x1,75P 1/2"-13UNC	16
GD-100-S		75	30	800	120+12	53	M16x2,0P	24

Options

						
Code Suffix	NYN	MCN	HUP	-FBL	-CEN	-CUR
Description	Nylon66(D70)	MC nylon(D80)	Cast PU(D70)	Black frame	Anti-static pad	PU pad
Available for	40 ~ 120	40 ~ 120	60 ~ 100	40 ~ 120	40 ~ 100	40 ~ 100