

# Control and signaling units

Harmony XB4, metal

Body/light assemblies for pilot lights with integral LED

To combine with:  
Heads, see [page 66](#)  
Contacts, see [page 76](#)

**Complete light bodies** (fixing collar + light block with integral LED)  
**Screw clamp terminal connections** (Schneider Electric anti-loosening system)

Light source	Supply voltage V	Color of light source	Reference	Weight kg/lb
Integral LED	12 ~ (50/60 Hz)	White	<b>ZB4BVJ1</b>	0.054/0.119
		Green	<b>ZB4BVJ3</b>	0.054/0.119
		Red	<b>ZB4BVJ4</b>	0.054/0.119
		Orange	<b>ZB4BVJ5</b>	0.054/0.119
		Blue	<b>ZB4BVJ6</b>	0.054/0.119
		24 ~ (1) (50/60 Hz)	White	<b>ZB4BVB1</b>
Green	<b>ZB4BVB3</b>		0.054/0.119	
Red	<b>ZB4BVB4</b>		0.054/0.119	
Orange	<b>ZB4BVB5</b>		0.054/0.119	
Blue	<b>ZB4BVB6</b>		0.054/0.119	
24...120 ~ (50/60 Hz)	White		<b>ZB4BVBG1</b>	0.054/0.119
	Green	<b>ZB4BVBG3</b>	0.054/0.119	
	Red	<b>ZB4BVBG4</b>	0.054/0.119	
	Orange	<b>ZB4BVBG5</b>	0.054/0.119	
	Blue	<b>ZB4BVBG6</b>	0.054/0.119	
	110...120 ~ (1) (50/60 Hz)	White	<b>ZB4BVG1</b>	0.054/0.119
Green		<b>ZB4BVG3</b>	0.054/0.119	
Red		<b>ZB4BVG4</b>	0.054/0.119	
Orange		<b>ZB4BVG5</b>	0.054/0.119	
Blue		<b>ZB4BVG6</b>	0.054/0.119	
230...240 ~ (1) (50/60 Hz)		White	<b>ZB4BVM1</b>	0.054/0.119
	Green	<b>ZB4BVM3</b>	0.054/0.119	
	Red	<b>ZB4BVM4</b>	0.054/0.119	
	Orange	<b>ZB4BVM5</b>	0.054/0.119	
	Blue	<b>ZB4BVM6</b>	0.054/0.119	

101239



ZB4BV●●

protected  
LED

(1) Complete bodies with Faston connector terminals ( 6.35 or 2 x 2.8mm/0.250 or 2x 0.110 in.), see [page 80](#).