

The Pride of Top Quality
FOOT MASTER®

Light duty casters



Guide for selection of wheels : Lighty duty casters


Image	Series	Description	Wheel code	Wheel dia mm	Wheel width mm	Axle bore mm	Hub length mm	Load capacity Kg	Bearing type
	TUN	<ul style="list-style-type: none"> – Injected polyurethane (Shore A92) – PP core – No bearing 	TUN-50-24	50	24	6	29	40	X
			TUN-64-24	64	24	6	29	50	X
			TUN-75-25	75	25	8	40	75	X
			TUN-100-30	100	30	8	40	100	X
			TUN-125-30	125	30	8	40	110	X
	TUS	<ul style="list-style-type: none"> – Injected polyurethane (Shore A92) – PP core – One ball bearing 	TUS-75-25	75	25	8	40	75	6202 ZZ
			TUS-100-30	100	30	8	40	100	6202 ZZ
			TUS-125-30	125	30	8	40	110	6202 ZZ
	TUD	<ul style="list-style-type: none"> – Injected polyurethane (Shore A92) – PP core – Two ball bearings 	TUD-100-30	100	30	8	30	100	608 ZZ
			TUD-125-30	125	30	8	30	110	608 ZZ
			TUD-150-30	150	30	8	30	110	608 ZZ
	HRN	<ul style="list-style-type: none"> – Injected rubber (Shore A85) – PP core – No bearing 	HRN-50-24	50	24	6	29	40	X
			HRN-64-24	64	24	6	29	50	X
			HRN-75-25	75	25	8	40	75	X
			HRN-100-30	100	30	8	40	100	X
	HRS	<ul style="list-style-type: none"> – Injected rubber (Shore A85) – PP core – One ball bearing 	HRS-75-25	75	25	8	40	75	6202 ZZ
			HRS-100-30	100	30	8	40	100	6202 ZZ
			HRS-125-30	125	30	8	40	110	6202 ZZ
	HRD	<ul style="list-style-type: none"> – Injected rubber (Shore A85) – PP core – Two ball bearings 	HRD-100-30	100	30	8	30	100	608 ZZ
			HRD-125-30	125	30	8	30	110	608 ZZ
			HRD-150-30	150	30	8	30	110	608 ZZ
	SUNS / SUND	<ul style="list-style-type: none"> – High elasticity polyurethane (Shore A70) – Nylon core – Two ball bearings (SUNS: one ball bearing) 	SUNS-75-25	75	25	8	40	90	6202 ZZ
			SUND-100-30	100	30	8	30	100	608 ZZ
			SUND-125-30	125	30	8	30	110	608 ZZ
	LUD	<ul style="list-style-type: none"> – Cast polyurethane (Shore A90) – Aluminum core – Two ball bearings 	LUD-75-30	75	30	8	30	90	608 ZZ
			LUD-100-30	100	30	8	30	120	608 ZZ
			LUD-125-30	125	30	8	30	120	608 ZZ
			LUD-150-30	150	30	8	30	120	608 ZZ
	LUD- WEU	<ul style="list-style-type: none"> – Cast polyurethane (Shore A90) – Aluminum core – Two ball bearings – Anti-static version (10⁸~10⁹Ωcm) 	LUD-WEU-75-30	75	30	8	30	90	608 ZZ
			LUD-WEU-100-30	100	30	8	30	120	608 ZZ
			LUD-WEU-125-30	125	30	8	30	120	608 ZZ
			LUD-WEU-150-30	150	30	8	30	120	608 ZZ
	LUP	<ul style="list-style-type: none"> – Cast polyurethane (Shore A90) – Aluminum core – Plain bearing 	LUP-75-17	75	17	10	22	75	Plain

FOOT MASTER®

Light duty casters

P series









 100~120kg  RoHS  -10~90°C



Brackets: Pressed steel plate, double ball bearing with hardened bearing seats in the swivel head, strong integrated pressed steel frame, dust protection cover in the swivel head, total-lock top brake system which is applied in wheel and swivel head simultaneously, bolted wheel axle structure

Surface Treatment: Zinc plated

* Recommended Load = Load Cap. × 3

Swivel	Rigid	Swivel with brake	Wheel type								
				mm	mm	Kg	mm	mm	mm	mm	mm
P-100-ASF	P-100-ARF	P-100-BSF	TUS	100	30	100	140	45	100x85	80x60 77x45	9
P-125-ASF	P-125-ARF	P-125-BSF		125	30	110	165	45			
P-100-ASF	P-100-ARF	P-100-BSF	HRS	100	30	100	140	45	100x85	80x60 77x45	9
P-125-ASF	P-125-ARF	P-125-BSF		125	30	110	165	45			
P-100-ASF	P-100-ARF	P-100-BSF	TUD	100	30	100	140	45	100x85	80x60 77x45	9
P-125-ASF	P-125-ARF	P-125-BSF		125	30	110	165	45			
P-100-ASF	P-100-ARF	P-100-BSF	HRD	100	30	100	140	45	100x85	80x60 77x45	9
P-125-ASF	P-125-ARF	P-125-BSF		125	30	110	165	45			
P-100-ASF	P-100-ARF	P-100-BSF	LUD	100	30	120	140	45	100x85	80x60 77x45	9
P-125-ASF	P-125-ARF	P-125-BSF		125	30	120	165	45			

Options

						
Code Suffix	TUS	HRS	TUD	HRD	LUD	-WEU
Description	Inj. PU(A92)	Rubber(A85)	Inj. PU(A92)	Rubber(A85)	Cast PU(A90)	Anti-static(Black)
Available for	100 ~ 125	100 ~ 125	100 ~ 125	100 ~ 125	100 ~ 125	100 ~ 125