

**TOP PLATE / THREADED STEM**

# 290 UMH

Medium-Heavy Duty Castor **SERIES**  
170 - 235 KGS



Option: Other colour on request

## Castor

**290** (American specification)  
Armor steel, double/reverse ballrace swivel path frame heat treatment  
Metal Finish: Black lacquer

## Wheel

**UMH** Hardness 94± Shore A (PU Yellow, non-marking, PP core black)  
Polyurethane, PP core double precision ball bearing (without threadguards)  
Temperature range: -20°C to +90°C

	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	daN
													kgs
	<b>291 UMH 100 P45</b>	113x100	84x74	11	136	42	100	40	12	51.5	***	***	170
	<b>291 UMH 125 P45</b>	113x100	84x74	11	163	42	125	40	12	51.5	***	***	205
	<b>291 UMH 150 P45</b>	113x100	84x74	11	190	42	150	40	12	51.5	***	***	235
	<b>292 UMH 100 P45</b>	113x100	84x74	11	136	RIGID	100	40	12	51.5	***	***	170
	<b>292 UMH 125 P45</b>	113x100	84x74	11	163	RIGID	125	40	12	51.5	***	***	205
	<b>292 UMH 150 P45</b>	113x100	84x74	11	190	RIGID	150	40	12	51.5	***	***	235
	<b>296 UMH 100 P45</b>	113x100	84x74	11	136	42	100	40	12	51.5	***	***	170
	<b>296 UMH 125 P45</b>	113x100	84x74	11	163	42	125	40	12	51.5	***	***	205
	<b>296 UMH 150 P45</b>	113x100	84x74	11	190	42	150	40	12	51.5	***	***	235
	<b>291 UMH 100 T16</b>	M16	30	136	42	100	40	12	51.5	***	***	***	170
	<b>291 UMH 125 T16</b>	M16	30	163	42	125	40	12	51.5	***	***	***	205
	<b>291 UMH 150 T16</b>	M16	30	190	42	150	40	12	51.5	***	***	***	235
	<b>296 UMH 100 T16</b>	M16	30	136	42	100	40	12	51.5	***	***	***	170
	<b>296 UMH 125 T16</b>	M16	30	163	42	125	40	12	51.5	***	***	***	205
	<b>296 UMH 150 T16</b>	M16	30	190	42	150	40	12	51.5	***	***	***	235