



**RNB series Non insulated ringTerminal**

connect one or two wires into a single point. The terminal is made by 99.99% high purity copper for good conductivity and has tin plating for corrosion resistance. Material for copper and insulation part is environmentally friendly, no-halogen, and high temperature resistant.

**Terminal Body:** Copper

**Brazed Seam**

**Plating:** Tin

**Material:** Copper

Item No.	Dimension							SQ wire (mm2)
	d2φ	B	L	F	E	Dφ	dφ	
RNB 1.25-3	3.2	5.7	12.6	4.95	4.8	3.4	1.7	0.5-1.5
RNBS 1.25-4	3.7	6.6	14.4	6.3				
RNB 1.25-5	5.3	8.0	15.8	7.0				
RNB 1.25-6	6.4	11.6	21.8	11.1				
RNB 1.25-8	8.4	11.6	21.8	11.1				
RNB 1.25-10	10.5	13.6	25.5	13.9				
RNB 1.25-12	13.0	19.2	31.0	16.5				
RNB 2-3	3.2	6.6	12.3	4.3	4.8	4.1	2.3	1.5-2.5
RNBS 2-4	4.3	6.6	16.0	7.0				
RNBS 2-5	5.3	8.5	16.8	7.75				
RNB 2-6	6.4	12.0	21.8	11.0				
RNB 2-8	8.4	12.0	21.8	11.0				
RNB 2-10	10.5	13.6	25.5	13.9				
RNB 2-12	13.0	19.2	31.0	16.5				
RNB 3.5-4	4.3	8.0	18.0	7.7	6.0	5.0	3.0	2.5-4.0
RNBS 3.5-5	5.3	8.0	18.0	7.7				
RNB 3.5-6	6.4	12.0	21.4	7.7				
RNB 5.5-5	5.3	9.5	19.8	8.3	6.8	5.6	3.4	4.0-6.0
RNB 5.5-6	6.4	12.0	25.8	13.0				
RNB 5.5-8	8.4	15.0	28.0	13.7				
RNB 5.5-10	10.5	15.0	28.0	13.7				
RNB 5.5-12	13.0	19.2	32.4	16.0				

Item No.	Dimension (mm)							SQ wire (mm <sup>2</sup> )
	d2∅	B	L	F	E	D∅	d∅	
RNBS 8-6	6.4	12.0	23.8	9.3				
RNB 8-8	8.4	15.0	29.8	13.8	8.5	7.2	4.5	6.0-10
RNB 8-10	10.5	15.0	29.8	13.8				
RNB 14-8	8.4	16.0	32.8	14.5	10.5	9.0	5.8	10-16
RNB 14-10	10.5	16.0	32.8	14.5				
RNBS 22-6	6.4	12.2	33.7	14.5				
RNB 22-8	8.4	16.5	33.7	13.5	12.0	11.5	7.7	16-25
RNB 22-10	10.5	16.5	33.7	13.5				
RNBS 38-8	8.4	15.3	39.0	18.3				
RNBS 38-10	10.5	15.3	39.0	18.3	14.0	13.3	9.4	35-50
RNB 38-12	13.0	22.0	42.7	17.7				
RNB 60-12	13.0	22.0	49.7	20.7	18.0	15.4	11.4	50-70
RNB 60-14	15.0	32.0	57.5	23.5				
RNB 70-12	13.0	24.0	51.0	20.0	19.0	17.5	13.3	70-95
RNB 70-14	15.0	32.0	61.0	26.0				
RNB 80-12	13.0	27.0	54.2	20.7	20.0	19.5	14.5	95-120
RNB 80-14	15.0	32.0	68.0	32.0				
RNB 100-12	13.0	28.5	55.6	20.4	21.0	22.1	16.4	120-150
RNB 100-14	15.0	32.0	69.0	32.0				
RNB 100-16	17.0	32.0	69.0	32.0				
RNB 150-14	15.0	36.0	66.0	23.0	27.0	26.6	19.5	150-185
RNB 150-16	17.0	36.0	66.0	23.0				
RNB 180-14	15.0	38.5	69.0	24.5	28.5	28.6	21.0	185-240
RNB 180-16	17.0	38.5	69.0	24.5				
RNB 200-14	15.0	44.0	72.0	24.5	31.5	32.6	24.0	240-300
RNB 200-16	17.0	44.0	72.0	24.5				
RNB 200-18	19.0	44.0	91.0	37.5				
RNB 325-16	17.0	50.5	88.0	33.5	35.5	37.1	28.0	300-400
RNB 325-18	19.0	50.5	105.7	45.0				
RNB 325-20	21.0	50.5	105.7	45.0				