




LED RECESSED DOWNLIGHT PRDYY Series



Note:

- Published lumen is total luminous flux of luminaire
- PF ≥ 0.5
- Lifespan: 25,000 hours
- CRI ≥ 80

≥ 0.5	80Ra	IP20	25,000 Hours	AC100 240V	50-60Hz
Power factor	CRI	Protection grade	Lifespan	Voltage	Frequency

Outstanding features

- Bridgelux/Samsung
- High quality PC diffuser cover
- 3000K(Warm white) / 4200K(Neutral white) / 6500K(Cool daylight)
- Compatible with Emergency Backup Battery
- Flicker-free
- High quality material and exceptional energy saving performance
- No UV radiation
- Minimise blue light emission

SPECIFICATION AND PRICE

Model	PRDYY108L5	PRDYY118L7	PRDYY138L9	PRDYY178L12	PRDYY188L20
LED chip	Bridgelux/Samsung				
Wattage (W)	5W	7W	9W	12W	20W
Efficacy (Lm/W)	85	95	100	110	110
Lumen (Lm)	425	665	900	1320	2200
Color temperature (K)	3000/4200/6500				
Dimensions (mm) (WxH)	108x32	118x32	138x32	178x36	188x36
Ceiling cut-out (mm)	90	90	115	155	160
Unit price (USD)	\$9.35	\$10.43	\$11.48	\$15.96	\$28.91

Suggested installation areas

