




LED



LED SURFACE DOWNLIGHT PSDH Series



Note:

- Published lumen is total luminous flux of luminaire
- PF ≥ 0.9
- Lifespan: 50,000 hours
- CRI ≥ 80

≥ 0.9	80Ra	IP20	50,000 Hours	AC100 240V	50-60Hz
Power factor	CRI	Protection grade	Lifespan	Voltage	Frequency

Outstanding features



Bridgelux/Samsung



High quality aluminium alloy heatsink



3000K(Warm white) / 4200K(Neutral white) / 6500K(Cool daylight)



High color rendering



Flicker-free



Low glare



No UV radiation



Minimise blue light emission

SPECIFICATION AND PRICE

Model	 PSDH113L7	 PSDH168L12	 PSDH218L18
LED chip	Bridgelux/Samsung		
Wattage (W)	7W	12W	18W
Efficacy (Lm/W)	130	130	130
Lumen (Lm)	910	1560	2340
Color temperature (K)	3000/4200/6500		
Dimensions (mm) (WxH)	113x32	168x32	218x32
Installation	Surface		
Unit price (USD)	\$20.13	\$32.04	\$40.43

Suggested installation areas



Apartment



Supermarket



Retail Store



Office



Hotel



School



Hospital