

Bảng thông số sản phẩm

Thông số kỹ thuật



240V Shaver Socket, White

A84727_WE

⚠ Ngừng sản xuất vào: 30 tháng sáu 2023

⚠ Ngừng sản xuất

Main

Range	ZENcelo
Product or component type	Shaver socket
Installation direction	Vertical
Input voltage	240 V AC 50/60 Hz
Output voltage	115 V AC 50/60 Hz 240 V AC 50/60 Hz
Material	Polycarbonate: grid plate Polycarbonate: surround Polycarbonate: bracket Brass: terminals
Colour tint	White

Complementary

Device mounting	Surface Flush
Cable cross section	1...2.5 mm ²
Rated operational power in VA	20 VA
Connections - terminals	Pillar terminals
Width	70 mm
Height	120 mm
Depth	51.9 mm

Environment

Ambient air temperature for operation	-5...45 °C
Ambient air temperature for storage	0...60 °C
Relative humidity	0...95 %
Environmental characteristic	UV resistant
Operating altitude	<= 2000 m
IP degree of protection	IP21
Standards	IEC 61558-2-5

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5 cm
Package 1 Width	7 cm
Package 1 Length	12 cm
Package 1 Weight	501 g
Unit Type of Package 2	CAR
Number of Units in Package 2	18
Package 2 Height	5 cm
Package 2 Width	7 cm
Package 2 Length	12 cm
Package 2 Weight	10245.4 g
Unit Type of Package 3	PAL
Number of Units in Package 3	900
Package 3 Height	95 cm
Package 3 Width	80 cm
Package 3 Length	120 cm
Package 3 Weight	535000 g

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information

Thay thế được đề xuất

Bảng thông số sản phẩm

Thông số kỹ thuật



240V Shaver Socket, Silver Bronze

A84727_SZ

⚠ Ngừng sản xuất vào: 30 tháng sáu 2023

⚠ Ngừng sản xuất

Main

Range	ZENcelo
Product or component type	Shaver socket
Installation direction	Vertical
Input voltage	240 V AC 50/60 Hz
Output voltage	115 V AC 50/60 Hz 240 V AC 50/60 Hz
Material	Polycarbonate: grid plate Polycarbonate: surround Polycarbonate: bracket Brass: terminals
Colour tint	Silver bronze

Complementary

Device mounting	Surface Flush
Cable cross section	1...2.5 mm ²
Rated operational power in VA	20 VA
Connections - terminals	Pillar terminals
Width	70 mm
Height	120 mm
Depth	51.9 mm

Environment

Ambient air temperature for operation	-5...45 °C
Ambient air temperature for storage	0...60 °C
Relative humidity	0...95 %
Environmental characteristic	UV resistant
Operating altitude	<= 2000 m
IP degree of protection	IP21
Standards	IEC 61558-2-5

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5 cm
Package 1 Width	7 cm
Package 1 Length	12 cm
Package 1 Weight	501 g
Unit Type of Package 2	CAR
Number of Units in Package 2	18
Package 2 Height	5 cm
Package 2 Width	7 cm
Package 2 Length	12 cm
Package 2 Weight	10245.4 g
Unit Type of Package 3	PAL
Number of Units in Package 3	900
Package 3 Height	95 cm
Package 3 Width	80 cm
Package 3 Length	120 cm
Package 3 Weight	535000 g

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information

Thay thế được đề xuất