











### LED RECESSED DOWNLIGHT **PRDXX Series**





## Note:

- Published lumen is total luminous flux of luminaire
- PF ≥0.9
- Lifespan: 50,000 hours
- CRI ≥80

≥0.9	80Ra	IP20	50,000 Hours	AC100 240V	50-60Hz
Power factor	CRI	Protection grade	Lifespan	Voltage	Frequency

# **Outstanding features**

Cree/Nichia



Beam angle: 45°



Low glare



High quality aluminium alloy heatsink



Minimise blue light emission



3000K(Warm white) / 4200K(Neutral white) / 6500K(Cool daylight)



Compatible with Emergency Backup Battery



Energy saving

# **SPECIFICATION AND PRICE**

Model	PRDXX176L20	PRDXX176L30	
LED chip	Cree/Nichia		
Wattage (W)	20W	30W	
Efficacy (Lm/W)	90	90	
Lumen (Lm)	1800	2700	
Color temperature (K)	3000/4000/5000		
Dimensions (mm)	176x76	176x76	
Ceiling cut-out (mm)	168x168	168x168	
Unit Price (USD)	\$111.26	\$119.70	

#### Suggested installation areas

















CCT 2700K and compatibility with Triac, Dali, 1-10V dimmers are available upon request.