

Model	SKP-BC40HL(V3.0)	SKP-BC40HL-800(V3.0)
Input Voltage	AC 100~240V / 50 / 60Hz	AC 110V / 50Hz, 220V / 60Hz
Output Voltage	DC 40V / 32V / 24V 5.5A	DC 40V / 32V / 24V 9A
Power Consumption	220W	360W
Count	1~99	
Count method	Count-up/Count-down	
Reverse Resuming	ON/OFF	
Work with Sensor	ON/OFF	
GATE Sensor	ON(2Sensor)/OFF(1Sensor)	
Slow-start time adjustable	0~9.9 seconds	
Slow-start speed adjustable	LO: 100%, 35%~85% L1-L9 Rated Speed	
Running Time limit-LO	0.00~9.99 seconds	
Running Time limit-HI	0.0~9.9 seconds	
Reminder Mode	ON/OFF/FF/EF with LED and buzzer	
Auto ZERO	ON/OFF	
External inputs	Forward/Reverse/Disable/Confirm/Sensor/Clear	
External outputs	OK/NG/OK ALL	
Screwdriver Control	HI/LO: Slow-Start	
Outside Dimensions	247X130X100(mm)	
Weight (g)	2.4	
Accessories	Power cordX1 KeyX2	
Remark	   	
Applicable Models	SKD-BN200 SKD-BN500 SKD-BN800	FOR ALL SKD-BN SERIES (included RBN, TBN, BN900)