




**LED**



## RECESSED REFLECTIVE LUMINAIRE (T-bar) PRFB Series



### Note:

- Published lumen is total luminous flux of luminaire
- PF ≥ 0.9
- Lifespan: 50,000 hours
- CRI ≥ 80

≥0.9	80Ra	IP20	50,000 Hours	AC220 240V	50-60Hz
Power factor	CRI	Protection grade	Lifespan	Voltage	Frequency

### Outstanding features

- LED chip from Bridgelux/Epistar
- Pre-anodized aluminium reflector
- 3000K(Warm white) / 4200K(Neutral white) / 6500K(Cool daylight)
- Lamp holder and accessories by BJB - Germany
- Compatible with Emergency Backup Battery
- Low glare
- Easy installation and maintenance
- Minimise blue light emission

## SPECIFICATION AND PRICE

Model	PRFB218L20	PRFB318L30	PRFB418L40	PRFB236L36	PRFB336L54	PRFB436L72
Lamp type	2x10W	3x10W	4x10W	2x20W	3x20W	4x20W
Efficacy (Lm/W)	80	80	80	80	80	80
Lumen (Lm)	1600	2400	3200	3200	4800	6400
Color temperature (K)	3000/4200/6500					
Wattage (W)	20W±2	30W±3	40W±4	40W±4	60W±6	80W±8
Operating temperature	-20~40°C					
Dimensions (mm) (LxWxH)	606x302x88	606x606x88	606x606x88	1216x302x88	1216x606x88	1216x606x88
Unit price (USD)	<b>\$38.00</b>	<b>\$58.30</b>	<b>\$72.43</b>	<b>\$53.70</b>	<b>\$85.48</b>	<b>\$106.00</b>

### Suggested installation areas



Apartment



Supermarket



Retail Store



Office



Hotel



School



Hospital

- Unit price includes LED tube

(10W-1250lm, 20W-2500lm, PF>0.9, Lifespan 50,000 hours)