


FEMALE PRE-INSULATING JOINT (FDD)




Insulation: Vinyl
Raw material: Brass
Plating: Tin



Item No.	Wire Range mm2 (A.W.G.)	Connecting spec. (mm)	Thickness (mm)	Dimension (mm)				Color	
				B	dφ	Dφ	L		H
FDD 1.25-110(5)		0.5 x 2.8	0.3	3.8	4.3	1.7	19.0	10.0	
FDD 1.25-110(8)		0.8 x 2.8	0.3	3.8	4.3	1.7	19.0	10.0	
FDD 1.25-187(5)	0.5-1.5 (22-16)	0.5 x 4.75	0.35	5.6	4.3	1.7	19.0	10.0	Red
FDD 1.25-187(8)		0.8 x 4.75	0.35	5.6	4.3	1.7	19.0	10.0	
FDD 1.25-205		0.5 x 5.2	0.35	6.5	4.3	1.7	20.0	10.0	
FDD 1.25-250		0.8 x 6.35	0.4	7.4	4.3	1.7	21.0	10.0	
FDD 2-110(5)		0.5 x 2.8	0.3	3.8	4.9	2.3	19.0	10.0	
FDD 2-110(8)		0.8 x 2.8	0.3	3.8	4.9	2.3	19.0	10.0	
FDD 2-187(5)	1.5-2.5 (16-14)	0.5 x 4.75	0.35	5.6	4.9	2.3	19.0	10.0	Blue
FDD 2-187(8)		0.8 x 4.75	0.35	5.6	4.9	2.3	19.0	10.0	
FDD 2-205		0.5 x 5.2	0.35	6.5	4.9	2.3	20.0	10.0	
FDD 2-250		0.8 x 6.35	0.4	7.4	4.9	2.3	21.0	10.0	
FDD 2-312		0.8 x 8.0	0.4	9.0	4.9	2.3	23.0	10.0	
FDD 5.5-187(5)		0.5 x 4.75	0.4	5.6	6.7	3.4	23.0	13.0	
FDD 5.5-312	4-6 (12-10)	0.8 x 8.0	0.5	9.0	6.7	3.4	27.0	13.0	Yellow
FDD 5.5-250		0.8 x 6.35	0.4	7.4	6.7	3.4	24.0	13.0	
FDD 5.5-375		1.2 x 9.4	0.5	10.9	6.7	3.4	29.6	13.0	

WIRE NUT CONNECTOR (SP)



Insulation: Vinyl
Raw material: Brass
Plating: Tin



Item No.	Cable Range	Dimension (mm)			Color
		B	C	L	
SP71	Min 0.75 x 1 + 0.5 x 1	8.5	6.7	15	Gray
SP72	Min 0.75 x 3	10.1	7.4	17.5	Blue
SP73	Min 0.75 x 3	12.6	9.9	22.1	Orange
SP74	Min 0.25 x 1 + 0.75 x 1	13.7	11	24.5	Yellow
SP75	Min 0.25 x 2	16	13	26.5	Red