

TERMINAL BLOCK CONNECTOR (TBS)



Material:

PE, Working Temperature:

- 40°C to 65°C, short time is 80°C.

PP, Working Temperature:




- 30°C to 90°C, short time is 110°C.

PA, Working Temperature:

- 35°C to 120°C, short time is 140°C.

Brass, Iron screw

Voltage: 250 - 450V



U Type

H Type

U TYPE




Item No.	L (mm)	W (mm)	H (mm)	A (mm)	B (mm)	Φ (mm)	Rated Voltage	Rated Current	Wire Range (mm ²)
TBS-3A	90.3	15.5	11.5	6	7.7	3.1	380V	3A	2.5-4.0
TBS-6A	110.5	15.5	12.4	6.5	9.5	3.2	380V	6A	4.0-6.0
TBS-10A	116.7	20	14.9	8	10	4	380V	10A	6.0-10.0
TBS-16A	136.8	21.5	16.7	10	11.7	4.2	380V	16A	10.0-12.0
TBS-20A	153.5	24.5	17.4	11.5	13.2	4.3	380V	20A	12.0-14.0
TBS-30A	164.6	25	18.8	12	14.1	5.5	380V	30A	16
TBS-60A	187.6	29	23.5	12	16	6.8	380V	60A	25
TBS-80A	205	33	27	15	17	7.0	400V	80A	35
TBS-100A	250	46	31	22	21	9.0	400V	100A	40

H TYPE



Item No.	L (mm)	W (mm)	H (mm)	A (mm)	B (mm)	Φ (mm)	Rated Voltage	Rated Current	Wire Range (mm ²)
TBS-3A	90.3	15.5	12	6	7.8	3.1	380V	3A	2.5-4.0
TBS-6A	111.4	15.5	13.5	6.5	9.6	3.2	380V	6A	4.0-6.0
TBS-10A	116.4	20	15.3	8	10	4	380V	10A	6.0-10.0
TBS-16A	133.8	22.7	16	10	11.5	4.2	380V	16A	10.0-12.0
TBS-20A	152.2	24.6	16	11.5	13.2	4.3	380V	20A	12.0-14.0
TBS-30A	162	25	19.3	12	13.9	5.5	380V	30A	16
TBS-60A	184.6	28.6	23	12	15.8	6.8	380V	60A	25

VINYL END CAPS (V)



Material: Made from PVC

Character: Clearly color, shine, soft, insulated

Color: Red, white, blue yellow, black, green, brown available upon special request.



Item No.	Dimension(mm)				
	D1	D2	D3	L	F
V 1.25	2.8	3.3	3.1	13	7
V 2	3.3	4.5	3.7	15	7
V 3.5	4.2	5.7	4.1	20	8
V 5.5	4.8	5.7	5.2	20	8
V 8	6.2	7.2	6.2	20	9
V 14	7.5	10	8	27	11
V 22	10.5	12	9.5	30	15
V 38	12.5	14	11.8	36	16.5
V 60	15	16.8	13.5	39	19
V 70	16	17.5	14.5	43	20
V 80	17	19	16	47	22
V100	19	22	18	54	24
V 125	21	24	20	57	25
V 150	23	24.5	22	65	30
V 200	27	32	24	65	30
V 240	29	38	26.5	77	39
V 325	29	38	29	77	40
V 400	42	45	36	85	41
V 500	46	48	40	88	42
V 630	52	23-Feb	44	92	47